## SELECTOR SWITCH ACTUATOR KEY Ø22MM PLATINUM SERIES CHROMED PLASTIC, 2 POSITION, 0 < 1 WITH DIFFERENT KEY CODE



Product designation  Product type designation			Selector switch actuator key - 2 position LPCS34
General characteristics			
Colour		<del></del>	Black
Type of positions			Selector switch
Material			Polyamide
IEC degree of protection			IP66, IP67 and IP69K
Mechanical features			
Mechanical life		cycles	1000000
Mounting adapter			LPXAU120
Weight		g	60
UL technical data			
UL degree of protection			Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions			
Temperature			
Operating temperature			
	min	°C	-25
	max	°C	+70
Storage temperature			
	min	°C	-40
	max	°C	+85
Dimensions			

## 25.2 (0.99") (0.88")

Certif	ications	and	comp	oliance
_				

Com	nlia	nce
COIII	pna	1100

CSA C22.2 n° 14 IEC/EN/BS 60947-1

IEC/EN/BS 60947-5-1

UL508

## Certificates

CCC

cULus





SELECTOR SWITCH ACTUATOR KEY Ø22MM PLATINUM SERIES CHROMED PLASTIC, 2 POSITION, 0 < 1 WITH DIFFERENT KEY CODE

ETIM classification

ETIM 8.0

EC000222 -Front element for selector switch