

PRODUCT-DETAILS

S401M-K1.6

S401M-K1.6 Miniature Circuit Breaker



Informations générales

Extension du type de produit	S401M-K1.6
Code de produit	2CCS571001R0257
EAN	7612270101627
Description courte	S401M-K1.6 Miniature Circuit Breaker

Description longue	<p>SMISSLINE TP S400M are a current limiting miniature circuit breakers. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (B,C,D,K), configurations (1P,1P+N,2P,3P,3P+N), breaking capacities (up to 10 kA at 240/415 V AC) and rated currents (up to 63A). MCBs of the product range S400M are comply with IEC/EN 60898-1 for B,C and D characteristic and IEC/EN 60947-2 for C and K characteristic. The pluggable solution is only for the SMISSLINE TP System, allowing the use for commercial, industrial, and critical power applications.</p>
--------------------	---

Technique

Normes et standards	IEC/EN 60947-2
Tripping Characteristic	K
Tension	acc. to IEC 60898-1 240 V
Operational Voltage	Maximum (Incl. Tolerance) 254 V AC Minimum 12 V AC Minimum 12 V DC

Tension assignée d'isolement (U_i)	acc. to IEC/EN 60664-1 440 V
Tension assignée de tenue aux chocs (U_{imp})	4 kV
Type de tension	AC
Courant nominal (I_n)	1.6 A
Courant nominal de fonctionnement (I_e)	1.6 A
Rated Short-Circuit Capacity	(230 V) 10 kA (400 V) 10 kA
Pouvoir assigné de coupure ultime en court-circuit (I_{cu})	(230 V) 25 kA (400 V) 25 kA
Rated Short-Circuit Making Capacity (I_{cm})	(240 V AC) 52.5 kA (254 V AC) 30 kA
Pouvoir assigné de coupure de service en court-circuit (I_{cs})	(240 V AC) 15 kA (254 V AC) 7.5 kA
Rated Service Short-Circuit Breaking Capacity, in % of I_{cu} (I_{cs})	50 %
Fréquence (f)	50 ... 60 Hz
Fréquence assignée (f)	50 ... 60 Hz
Power Loss	1.6 W
Power Supply Connection	Arbitrary
Contact Position Indication	Red ON / Green OFF
Classe de limitation d'énergie	3
Electrical Endurance	10000 cycle
Mechanical Endurance	10000 cycle
Number of Protected Poles	1
Nombre de pôles	1
Catégorie de Surtension	III
Couple de serrage	2.8 N·m
Type de libération	K
Screw Terminal Type	Failsafe Bi-directional Cylinder-lift Terminal
Actuator Marking	I / O
Type d'encastrement	Any
Recommended Screw Driver	Pozidriv 2
Accessories Available	Oui
Connecting Capacity	Flexible 0.75 ... 25 mm ² Rigid 0.75 ... 35 mm ²
Type de borne	Screw Terminals

Environnement

Température de l'air Operation -25 ... 60 °C

ambiant

Reference Ambient Air Temperature 40 °C

Indice de protection IP20

Degré de pollution 3

Resistance to Vibrations acc. to IEC 60068-2-6 2...13.2 Hz/1 mm
13.2...100Hz/0.7 g, 5 cycles
5...150 ... 5 Hz/1 g, 4 waves

Statut RoHS Following EU Directive 2002/95/EC August 18, 2005 and amendment

Informations RoHS 9AKK107991A9634

Informations environnementales 9AKK108467A9561

Conflict Minerals Reporting Template (CMRT) 9AKK108468A3363

Dimensions

Width in Number of Modular Spacings 1

Produit Largeur Net 18 mm

Produit Hauteur Net 91 mm

Produit Longueur Net 75 mm

Poids net 110 g

Taille 1 module

Profondeur d'encastrement (t₂) 75 mm

Schéma dimensionnel 9AKK107492A6192

Commande

Emballage Niveau 1 Unités carton 10 pièce

Emballage Niveau 1 Poids 1165 g

E-Number (Switzerland) 809211807

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE 9AKK107991A9634

Installation

Instructions et manuels 2CCC451019M0109

Downloads Préférés

Fiche produit, informations techniques 9AKK107492A6192

Classifications

ETIM 8	EC000042 - Miniature circuit breaker (MCB)
ETIM 9	EC000042 - Miniature circuit breaker (MCB)
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85362020
eClass	V11.0 : 27141901
Code de classification d'objet	FC

Accessories

Identifiant	Description	Type	Quantity	Unit Of Measure
2CCS500900R0081	HK40011-L Auxiliary swtich	HK40011-L	1	piece
2CCS500900R0214	HK40011-R Auxiliary swtich	HK40011-R	1	piece
2CCF201112R0001	HK40020-L Auxiliary swtich	HK40020-L	1	piece
2CCF201114R0001	HK40002-L Auxiliary swtich	HK40002-L	1	piece
2CCF201113R0001	HK40020-R Auxiliary swtich	HK40020-R	1	piece
2CCF201115R0001	HK40002-R Auxiliary swtich	HK40002-R	1	piece
2CCS500900R0101	SK40011-L Signal contact	SK40011-L	1	piece
2CCS500900R0215	SK40011-R Signal contact	SK40011-R	1	piece
2CCF201162R0001	SK40020-L Signal contact	SK40020-L	1	piece
2CCF201164R0001	SK40002-L Signal contact	SK40002-L	1	piece
2CCF201163R0001	SK40020-R Signal contact	SK40020-R	1	piece
2CCF201165R0001	SK40002-R Signal contact	SK40002-R	1	piece
2CCS500900R0141	SK40010-LSA Signal contact	SK40010-LSA	1	piece
2CCF201212R0001	HK400 10-L SA Auxiliary swtich	HK40010-LSA	1	piece
2CCS500900R0216	SK40010-RSA Signal contact	SK40010-RSA	1	piece
2CCF201213R0001	HK400 10-R SA Auxiliary swtich	HK40010-RSA	1	piece
2CCS500900R0161	ZLS931 Spare parts	ZLS931	1	piece
2CCS500900R0021	NT401-63 Neutral disconnect terminal block	NT40163	1	piece
2CCS500900R0011	NT402-63 Neutral disconnect terminal block	NT40263	1	piece
2CDS200909R0001	S2C-A1 Shunt Trip	S2C-A1	1	piece
2CDS200909R0002	S2C-A2 Shunt Trip	S2C-A2	1	piece
2CCA880212R0001	CMS-122PS Sensor	CMS-122PS	1	piece
2CCA880102R0001	CMS-102PS Sensor	CMS-102PS	1	piece

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Plug-in Distribution Systems → Système Smisline → Miniature Circuit Breakers MCBs

