

PRODUCT-DETAILS

# P9PDNV0-AA

## P9PDNV0-AA Lamp Block



### Informations générales

|                              |  |
|------------------------------|--|
| Extension du type de produit | P9PDNV0-AA   |
| Code de produit              | 1SFA215831R1000  |
| EAN                          | 7320500522936  |
| Description courte           | P9PDNV0-AA Lamp Block  |
| Description longue           | The P9PDNV0-AA Lamp Block is: Modular metal - Lamp Block - Brown - Illuminated - Front mounting - 380 V<br>This Lamp Block is part of ABB's modular metal range designed for mining, construction and heavy industry applications, combining the highest reliability with the full flexibility of a modular range. |

### Commande

|                  |            |
|------------------|------------|
| Quantité minimum | 200 pièce  |
| Code douanier    | 8536619090 |

### Downloads Préférés

|  |                 |
|--|-----------------|
| Fiche produit, informations techniques | 1SFC151007C02_  |
| Instructions et manuels                | 1SFC151011M0201 |

## Dimensions

|                      |          |
|----------------------|----------|
| Produit Largeur Net  | 9.8 mm   |
| Produit Hauteur Net  | 39.5 mm  |
| Produit Longueur Net | 36.2 mm  |
| Poids net            | 0.063 kg |

## Technique

|                              |  |
|------------------------------|--|
| Température de l'air ambiant | Operation -30 ... 70 °C<br>Storage -40 ... +70 °C  |
| Couleur                      | Brown  |
| Voyant                       | Illuminated  |
| Type de lampe                | Lamp block for Ba9s socket for max 2W 380 V AC/DC LED  |
| Type de montage              | Front mounting   |
| Indice de protection         | Terminals IP20   |
| Fréquence assignée (f)       | 50 / 60 Hz   |
| Tension                      | Maximum 380 V  |
| Connecting Capacity          | Flexible with Ferrule 1 x 0.75...2.5 mm <sup>2</sup><br>Flexible with Ferrule 2 x 0.75...2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1 x 0.75...2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2 x 0.75...2.5 mm <sup>2</sup><br>Flexible 1 x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible 2 x 0.75 ... 2.5 mm <sup>2</sup><br>Solid 1 x 0.75...2.5 mm <sup>2</sup><br>Solid 2 x 0.75...2.5 mm <sup>2</sup> |
| Type de raccordement         | Screw Clamp  |
| Type de borne                | Screw Terminals  |
| Couple de serrage            | 0.9 N·m  |
| Wire Stripping Length        | 8 mm   |

## Technique UL/CSA

|                     |                |
|---------------------|----------------|
| Connecting Capacity | 1x 18...14 AWG |
| UL/CSA              | 2x 18...14 AWG |

## Environnement

|   |  |
|---|--|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658  |
| REACH Declaration                           | 2CMT2022-006479  |
| Informations RoHS                           | 2CMT2019-005862  |
| Statut RoHS                                 | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| WEEE B2C / B2B                              | Business To Business   |
| Catégorie DEEE                              | 5. Small Equipment (No External Dimension More Than 50 cm)             |

## Certificats et Déclarations (Numéro de document)

|                           |                     |
|---------------------------|---------------------|
| Certificat BV             | 2CMT2019-005867     |
| CB Certificate            | 2CMT2019-005874     |
| CQC Certificate           | CQC2013010304650811 |
| Certificat CSA            | 2CMT2019-005868     |
| Certificat ecULus         | 2CMT2019-005868     |
| Declaration of Conformity | 2020980304001860    |

- CCC

Déclaration de Conformité 2CMT2019-005862

- CE

Declaration of Conformity 2CMT2020-006121

- UKCA

DNV GL Certificate 2CMT2019-005876

Certificat RINA 2CMT2019-005866

Certificat UL 2CMT2019-005868

---

## Emballage

Emballage Niveau 1 bag 200 pièce  
UnitésEmballage Niveau 1 200 mm  
LargeurEmballage Niveau 1 50 mm  
LongueurEmballage Niveau 1 600 mm  
Hauteur

Emballage Niveau 1 Poids 12.6 kg

Emballage Niveau 1 EAN 7320500519332

---

## Classifications

ETIM 7 EC000204 - Lamp holder block for control circuit devices

ETIM 8 EC000204 - Lamp holder block for control circuit devices

eClass V11.0 : 27371209

UNSPSC 39122221

Code de catégorie granulaire IDÉA (IGCC) 5219 &gt;&gt; Switch part or accessory

---

## Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Unités de commande et de signalisation → Modular Metal Range P9M

