

PRODUCT-DETAILS

# OT400ES40K

## OT400ES40K SWITCH-DISCONNECTOR



### Informations générales

Extension du type de produit	OT400ES40K
Code de produit	1SCA022870R3780
EAN	6417019337401
Description courte	OT400ES40K SWITCH-DISCONNECTOR
Description longue	4-pole, side operated, base mounted switch-d disconnector with black direct mount handle, terminal bolt kit included

### Valeur Circulaire

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Instructions relatives à la fin de vie	1SCC301118M0201
Informations environnementales	1SCC301266D0201
Environmental Product Declaration - EPD	1SCC301283D0201
REACH Declaration	1SCC011021D0201
Informations RoHS	1SCC011020D0201
Toxic Substances Control Act - TSCA	1SCC011025D0201

---

## Eco Transparence

---

Environmental Product Declaration - EPD	1SCC301283D0201
---	-----------------

---



---

## Commande

---

Quantité minimum	1 pièce
Code douanier	85365080
Pays d'origine	Finland (FI)

---



---

## Downloads Préférés

---

Fiche produit, informations techniques	1SCC301020C0201
Instructions et manuels	1SCC301070M0207
Mechanical Drawings	1SCC301402F0001 1SCC301401F0001 OT315-400ES40K.stp OT315ES40K.igs
Environmental Product Declaration - EPD	1SCC301283D0201
Instructions relatives à la fin de vie	1SCC301118M0201

---



---

## Dimensions

---

Produit Largeur Net	295 mm
Produit Hauteur Net	185 mm
Produit Longueur Net	107 mm
Poids net	4.1 kg 9 lb

---



---

## Technique

---

Rated Operational Current AC-21A ( $I_e$ )	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A (1000 V) 400 A
Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Power AC-23A ( $P_e$ )	(220 ... 240 V) 132 kW (400 ... 415 V) 230 kW (500 V) 280 kW (690 V) 400 kW
Courant thermique conventionnel à l'air libre ( $I_{th}$ )	$\Theta = 40\text{ °C}$ 400 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 400 A
Tension assignée de tenue aux chocs ( $U_{imp}$ )	12 kV
Tension assignée d'isolement ( $U_i$ )	acc. to IEC/EN 60664-1 1000 V
Tension	Circuit principal 1000 V

Rated Short-Circuit Making Capacity ( $I_{cm}$ )	(690 V) 65 kA
Courant assigné de courte durée admissible ( $I_{cw}$ )	for 1 s 15 kA
Power Loss	at Rated Operating Conditions per Pole 10 W
Degré de pollution	3
Handle Color	Black
Handle Type	Direct mounted pistol type handle
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism at the End of the Switch 40 (Right Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Mode de fonctionnement	Side operated
Normes et standards	IEC 60947-3
Fonctions spéciales	No
Type de montage	Base mounting
Nombre de pôles	4
Indice de protection	Front IP00
Type de borne	Lug terminals
Couple de serrage	acc. IEC 60947-1 30 ... 44 N·m
Durabilité mécanique	16000
Lock Type	Yes

## Technique UL/CSA

Couple de serrage	acc. IEC 60947-1 30 ... 44 N·m
-------------------	--------------------------------

## Environnement

Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations environnementales	1SCC301266D0201
Toxic Substances Control Act - TSCA	1SCC011025D0201

## Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	1SCC301135D2704
DNV GL Certificate	1SCC301174D0204
REACH Declaration	1SCC011021D0201

## Emballage

Emballage Niveau 1 Unités	box 1 pièce
Emballage Niveau 1 Largeur	250 mm 9.8 in
Emballage Niveau 1 Longueur	290 mm 11.4 in

Emballage Niveau 1 Hauteur	170 mm 6.7 in
Emballage Niveau 1 Poids	4.3 kg 9.6 lb
Emballage Niveau 1 EAN	6417019337401

---

## Classifications

---

Code de classification d'objet	Q
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
eClass	V11.1 : 27371403
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Catégories

---

Produits basse tension → Interrupteurs → Interrupteurs-sectionneurs

