



HLTP/HLSP Hook and Loop Cable Ties – Plenum

- Soft, premium material is safe to use on high performance network cables protecting against over-tensioning
- UL Listed for use in plenum or air handling spaces (such as ceiling voids and underfloor areas) per NEC, Section 300-22 (C) and (D)
- Material flammability rating: UL 94V-2
- Adjustable, releasable, and re-usable – ideal for applications requiring frequent moves, adds, or changes
- Operating temperature range: 0°F – 122°F (-18°C – 50°C)



Part Number	Length		Width		Max. Bundle Dia.		Min. Loop Tensile Str.*		Std. Pkg. Qty.	Std. Ctn. Qty.
	In.	m	In.	mm	In.	mm	Lbs.	N		

UL Listed Loop Ties (Maroon) – Slot allows for pre-wrapping of bundles

HLTP2I-X12	8.00	203.0	0.50	12.7	1.91	49.0	40	178	10	100
HLTP3I-X12	12.00	305.0			3.18	81.0				

UL Listed Loop Ties (Black) – Slot allows for pre-wrapping of bundles

HLTP2I-X0	8.00	203.0	0.50	12.7	1.91	49.0	40	178	10	100
HLTP3I-X0	12.00	305.0			3.18	81.0				

UL Listed Strip Ties (Maroon) – Perforated in convenient 6", 12", and 18" strips

HLSP1.5S-X12	6.00	152.0	0.75	19.1	1.50	38.0	50	222	10	100
HLSP3S-X12	12.00	305.0			3.20	81.0				
HLSP5S-X12	18.00	457.0			5.00	127.0				

UL Listed Strip Ties (Black) – Perforated in convenient 6", 12", and 18" strips

HLSP1.5S-X0	6.00	152.0	0.75	19.1	1.50	38.0	50	222	10	100
HLSP3S-X0	12.00	305.0			3.20	81.0				
HLSP5S-X0	18.00	457.0			5.00	127.0				

For color options, reference Hook & Loop cable ties chart, see page P.5.
*Note: Minimum 2" overlap required to achieve loop tensile rating.

CE Tak-Tape™ Hook & Loop Cable Tie Rolls

- Strong, low profile, flexible material is safe to use on high performance cabling protecting against over-tensioning
- Adjustable, releasable, and re-usable
- Cost-effective for general purpose bundling
- Continuous rolls can be easily cut to size – Panduit cutter included with TTR-35RX0
- Leaves no residue
- Available in black color
- Operating temperature range: 0°F – 220°F (-17°C – 104°C)
- Complementary mounts available, see page P.9



Part Number	Length		Width		Max. Bundle Dia.		Min. Loop Tensile Str.*		Std. Pkg. Qty.	Std. Ctn. Qty.
	Ft.	m	In.	mm	In.	mm	Lbs.	N		
TTR-20R0	20.0	6.1	0.75	19.1	Various	Various	40	178	1	10
TTR-35R3-0	35.0	10.7								8
TTR-35RX0										10

Standard Package Quantity for TTR-35R3-0 is 1 package of three 35' rolls, TTR-35RX0 is 1 package of ten 35' rolls.
For color options, reference Hook & Loop cable ties chart, see page P.5.
*Note: Minimum 2" overlap required to achieve loop tensile rating.

A. Featured Products

B. Copper Systems

C. Fiber Systems

D. Faceplates, Frames & Surface Mount Boxes

E. Industrial Networks

F. Audio Video Systems

G. Keystone Cabling Systems

H. Zone Cabling

J. Cable Routing Systems

K. Surface Raceway

L. Cabinets & Rack Systems

M. Power Management

N. Grounding & Bonding

O. Identification Products

P. Cable Management Accessories

Q. Part Number Index