

Product type designation				GX20
General characteristics				
Switching diagram				10
N° of elements				2
Contact characteristics				
Rated insulation voltage U_i	IEC/EN	V	690	
	UL/CSA	V	600	
Rated impulse withstand voltage U_{imp}			kV	6
Conventional free air thermal current I_{th}	UL/CSA	A	15	
Rated operational voltage			V	440
Maximum fuse size for short-circuit protection I_n (gG)			25kA	A 16
			1s	A 250
Operational current I_e IEC/EN	AC1/AC21A		A	20
	AC15		110V	A 10
			220/230V	A 8
			660/690V	A 3.7
Rated operational power in AC	Single-phase AC-3		380/440V	kW 3
	Three-phase AC23A		380/440V	kW 7.5
	Single-phase AC23A		380/440V	kW 3.5
			380/440V	kW 3.5
Rated operational current in DC	DC21A		48V	A 20
			60V	A 20
			110V	A 4
			440V	A 0.25
	DC23A (poles in series)		24V	A 20 (1)
			48V	A 20 (2)
			60V	A 20 (3)
			110V	A 10 (3)
			220V	A 8 (4)
	DC13		24V	A 20
			48V	A 16
			60V	A 12
			110V	A 1
		220V	A 0.4	
		440V	A 0.15	
Mechanical features				
Terminals screw				M3
Tightening torque for terminals max				Nm 0.8
Conductor size				

AWG - Rigid cable

min	AWG	20
Max	AWG	14

AWG - Flexible cable

min	AWG	20
-----	-----	----

Conductor size (IEC) - Flexible cable

min	mm ²	0.5
Max	mm ²	2.5

Conductor size (IEC) - Rigid cable

Max	mm ²	2.5
-----	-----------------	-----

Mechanical life

cycles	5x10 ⁶
--------	-------------------

UL technical data

Motor power for direct-on-line control

for three-phase motor

240V	HP	3
480V	HP	5
600V	HP	5

for single-phase motor

120V	HP	0.75
240V	HP	1.5

Ambient conditions

Temperature

Operating temperature

min	°C	-25
max	°C	+55

Storage temperature

min	°C	-40
max	°C	+70

Resistance & Protection

Frontal IP degree

IP65

Terminals IP degree

IP20

ETIM classification

ETIM 8.0

EC001029 -
Selector switch,
complete