

68 Q-MC range

Energy and services distribution pedestals in insulating material

Six different types of pedestals for electricity distribution, with socket-outlets complying with the IEC 309 Standard or terminal block output, also for the distribution of water, TV and telephone signals, and data.

- High resistance to mechanical, chemical and atmospheric agents and UV rays.
- Electric circuits and terminal blocks are contained in separated, watertight compartments to guarantee protection against water, damp and dust.
- Versions for centralized and prepaid with electronic management system.
- Versions that can be customized on demand, wired and certified.



68 Q-MC RANGE

ENERGY AND SERVICES DISTRIBUTION PEDESTALS IN INSULATING MATERIAL

WIRED DISTRIBUTION PEDESTALS

EXAMPLES OF APPLICATION							TYPE	IMAGE	BLUE VERSION	WHITE VERSION	IP DEGREE	MAIN SWITCH				
Harbours	Campsites	Urban areas	Gardens, parks	Block of flats	Road shows	Industrial areas						SWITCH DISCONNECTOR				
												2P	3P	4P		
			•	•			Q-MC 16 B PEDESTAL			GW 68 841 A	GW 68 841 W	56				
											GW 68 842 A	GW 68 842 W	56			
					•		Q-MC 16 T PEDESTAL			GW 68 846 A	GW 68 846 W	55				
											GW 68 847 A	GW 68 847 W	56			
•		•		•		•	Q-MC 63 B PEDESTAL			GW 68 851 A	GW 68 851 W	56			1 x 32A	
											GW 68 852 A	GW 68 852 W	56			1 x 32A
•	•	•		•		•	Q-MC 63 E ELECTRONICS PEDESTAL			GW 68 876 A	GW 68 876 W	56			1 x 32A	
											GW 68 877 A	GW 68 877 W	56			1 x 32A
											GW 68 878 A	GW 68 878 W	56			1 x 63A
•	•										GW 68 874 A	GW 68 874 W	56			
											GW 68 875 A	GW 68 875 W	56			
	•						Q-MC 63 C PEDESTAL			GW 68 856 A	GW 68 856 W	55	1 x 32A			
											GW 68 857 A	GW 68 857 W	56	1 x 40A		
											GW 68 858 A	GW 68 858 W	55	1 x 32A		
•		•		•		•	Q-MC 125 B PEDESTAL			GW 68 801 A	GW 68 801 W	44			1 x 32A	
											GW 68 802 A	GW 68 802 W	44			1 x 63A
											GW 68 803 A	GW 68 803 W	56			1 x 63A
•	•					•	Q-MC 200 B PEDESTAL			GW 68 831 A	GW 68 831 W	44			1 x 32A	
											GW 68 832 A	GW 68 832 W	44			1 x 32A
											GW 68 833 A	GW 68 833 W	44			1 x 32A
•	•						Q-MC 200 E ELECTRONICS PEDESTAL			GW 68 867 A	GW 68 867 W	55				

68 Q-MC RANGE


	TYPE AND NO. SOCKETS INSTALLED						NO. OF MODULAR PROTECTION AND MONITORING DEVICES						
	NON-INTERLOCKED	IEC 309 INTERLOCKED			SPECIAL SOCKETS	ITALIAN/GERMAN STANDARD DOMESTIC SOCKETS	RCD 30mA AC		MINIATURE CIRCUIT BREAKERS C CHARACTERISTIC 6kA		RESIDUAL CURRENT CIRCUIT BREAKERS 30mA AC		
		2P+⊥	2P+⊥	3P+⊥			3P+N+⊥	RJ45+ TV/SAT	2P+⊥ 10/16A	2P	4P	2P	3P
		2 x 16A										1 x 16A	
		1 x 16A				2						1 x 16A	
	6 x 16A					2		1 x 40A	4 x 16A				
		2 x 16A	1 x 16A			2		1 x 40A	3 x 16A	1 x 16A			
		4 x 16A										4 x 16A	
		2 x 16A 2 x 32A										2 x 16A 2 x 32A	
		4 x 16A										4 x 16A	
		3 x 16A		1 x 16A								3 x 16A	1 x 16A
		4 x 32A										4 x 32A	
				2 x 63A									2 x 63A
				1 x 125A				Earth leakage relay with external toroid	MT HP 4P C125 16kA				
		4 x 16A										4 x 6A	
	8 x 16A											8 x 6A	
	4 x 16A				4+4							4 x 6A	
		4 x 16A										4 x 16A	
		2 x 16A		2 x 16A								2 x 16A	2 x 16A
		1 x 16A		2 x 32A								1 x 16A	2 x 25A
		4 x 16A										4 x 10A	
		6 x 16A										6 x 10A	
		8 x 16A										8 x 10A	
	Direct coupling without socket							Earth leakage relay with external toroid	MTX 4P 250A Type N 36kA				


68 Q-MC RANGE

68 Q-MC RANGE








ENERGY AND SERVICES DISTRIBUTION PEDESTALS IN INSULATING MATERIAL

FIRE-FIGHTING PEDESTALS


	BLUE VERSION	WHITE VERSION	CONFIGURATION
	GW 68 721 A	GW 68 721 W	FITTED FOR 6KG FIRE EXTINGUISHER
	GW 68 723 A	GW 68 723 W	FITTED FOR 9KG FIRE EXTINGUISHER
	GW 68 722 A	GW 68 722 W	FITTED FOR LANCE, HOSE AND SUPPORT
	GW 68 729 A	GW 68 729 W	FITTED FOR LANCE, HOSE, SUPPORT AND 6KG FIRE EXTINGUISHER
GW 68 779			KIT CONTAINING LANCE, 15M HOSE AND SUPPORT

	BLUE VERSION	WHITE VERSION	TYPE	CONFIGURATION
	GW 68 726 A	GW 68 726 W	standard	SUITABLE FOR LANCE, SUPPORT AND HOSE
	GW 68 728 A	GW 68 728 W	high capacity	
GW 68 780				KIT CONTAINING LANCE, 20M HOSE, AND SUPPORT




EMPTY DISTRIBUTION PEDESTALS

	TYPE	BLUE VERSION	WHITE VERSION	EN 50022 MODULES	TYPE OF TAPPING	SIDE A	SIDE B
	Q-MC 16 B PEDESTAL	GW 68 701 A	GW 68 701 W	18 (9x2)	Single-sided	Empty compartment that can be equipped with 1 panel	Empty compartment that can be equipped with 1 water kit
		GW 68 711 A	GW 68 711 W	18 (9x2)	Double-sided	Empty compartment that can be equipped with 1 panel	Empty compartment that can be equipped with 1 panel
	Q-MC 16 T PEDESTAL	GW 68 712 A	GW 68 712 W	18 (9x2)	Double-sided	Empty compartment that can be equipped with 1 panel	Empty compartment that can be equipped with 1 panel
	Q-MC 63 B PEDESTAL	GW 68 713 A	GW 68 713 W	18 (9x2)	Double-sided	Empty compartment that can be equipped with 1 panel	Empty compartment that can be equipped with 1 panel
	Q-MC 63 C PEDESTAL	GW 68 714 A	GW 68 714 W	18 (9x2)	Double-sided	Empty compartment that can be equipped with 1 panel	Empty compartment that can be equipped with 1 panel
	Q-MC 63 C PEDESTAL	GW 68 716 A	GW 68 716 W	36 (9x4)	Double-sided	Empty compartment that can be equipped with 2 panels	Empty compartment that can be equipped with 2 panels
	Q-MC 125 B PEDESTAL	GW 68 715 A	GW 68 715 W	14	Single-sided	Empty compartment with blank retractable door that can be equipped with 1 panel	Empty compartment with blank retractable door that can be equipped with 1 panel
	Q-MC 200 B PEDESTAL	GW 68 717 A	GW 68 717 W	28 (14x2)	Double-sided	Empty compartment with blank retractable door that can be equipped with 2 panels	Empty compartment with blank retractable door that can be equipped with 2 panels

COMPONENTS FOR Q-MC 16 B, 16 T, 63 B AND 63 C

TYPES OF PANELS					
FOR SBF INTERLOCKED SWITCHED SOCKET-OUTLET ASSEMBLY				FOR NON-INTERLOCKED SOCKET-OUTLET ASSEMBLY	
BLUE VERSION	WHITE VERSION	TYPE	NO.	TYPE	NO.
	GW 68 745 W	67 IB range Vertical IP67 16/32A	2		
GW 68 746 A	GW 68 746 W	44 IB range Horizontal IP44 16/32A	2		
GW 68 747 A	GW 68 747 W	Combibloc range IP44/55 16/32A	2	IEC 309 range, flush-mounting 16/32A or 85x75mm flanged lids	1
GW 68 748 A	GW 68 748 W			IEC 309 range, flush-mounting 16/32A or 85x75mm flanged lids	4
GW 68 749 A	GW 68 749 W	67 IB range Vertical IP67 63A	1		
GW 68 750 A	GW 68 750 W	blank			

COMPONENTS FOR Q-MC 125 B AND 200 B

TYPES OF PANELS					
FOR SBF INTERLOCKED SWITCHED SOCKET-OUTLETS ASSEMBLY				FOR NON-INTERLOCKED SOCKET-OUTLET ASSEMBLY	
BLUE VERSION	WHITE VERSION	TYPE	NO.	TYPE	NO.
	GW 68 731 W	67 IB range Vertical IP67 16/32A	3		
	GW 68 732 W	44 IB range Horizontal IP44 16/32A	4		
	GW 68 733 W	Combibloc range IP44/55 16/32A	3	IEC309 flush-mounting sockets 16/32A and 85x75mm flanged lids	2
	GW 68 734 W			IEC309 flush-mounting sockets 16/32A and 85x75mm flanged lids	6
	GW 68 735 W	67 IB range Vertical IP67 63A	2		
	GW 68 736 W			IEC309 flush-mounting sockets 125A	1
GW 68 737 A	GW 68 737 W	blank			
GW 68 741 A	GW 68 741 W	14-module control unit panel EN 50022			

68 Q-MC RANGE