

LL3-DC47

**FIBERS** 





#### Ordering information

Туре	Part no.
LL3-DC47	5324268

Included in delivery: BF-WLL160-10 (1), FC (1)
Other models and accessories → www.sick.com/LL3

#### Detailed technical data

#### **Features**

Device type	Fibers
Functional principle	Proximity system
For fiber-optic sensor	GLL170(T), WLL180
Fiber length	2,000 mm
Fiber material	Polymethylmethacrylat (PMMA)
Jacket material	Polyethylen (PE)
Fiber head material	Stainless steel
Outer diameter, fiber-optic cable connection	1 mm
Fiber-optic cable cuttable	✓
Fiber-optic head design	Flat type, 90° deflection
Fiber arrangement	Monofiber
Core structure	2 x Ø 0,5 mm Monofiber
Angle of dispersion < 60°	No
Compatibility with infrared light (1,450 nm)	No
Application	High flexible (static)
Highly flexible/elastic fibers (bend radius 1–4 mm)	Yes
Adapter end sleeves required	Yes
Angle of dispersion	60°
Integrated lens	No
Minimal object diameter	0.01 mm <sup>1)</sup>
Included with delivery	Adapter sleeves, BF-WLL160-10 (1.0 mm) adapter sleeves, FC fiber cutter (5304141)
Compatibility tip adapters	No

 $<sup>^{1)}</sup>$  Minimum detectable object was determined at optimum measuring distance and optimum setting.

#### Mechanics/electronics

Bend radius, fibre-optic cable	1 mm
Ambient operating temperature	-40 °C +60 °C

#### Classifications

ECLASS 5.0	27270905
------------	----------

ECLASS 5.1.4	27270905
ECLASS 6.0	27270905
ECLASS 6.2	27270905
ECLASS 7.0	27270905
ECLASS 8.0	27270905
ECLASS 8.1	27270905
ECLASS 9.0	27270905
ECLASS 10.0	27270905
ECLASS 11.0	27270905
ECLASS 12.0	27270905
ETIM 5.0	EC002651
ETIM 6.0	EC002651
ETIM 7.0	EC002651
ETIM 8.0	EC002651
UNSPSC 16.0901	39121528

## Sensing ranges with WLL180T

Operating mode 16 µs	12 mm
Operating mode 70 µs	25 mm
Operating mode 250 µs	37 mm
Operating mode 2 ms	75 mm
Operating mode 8 ms	90 mm
Note	Sensing ranges related to fiber-optic sensors with type of light: visible red light

## Sensing ranges with GLL170


Operating mode 250 µs	32 mm
-----------------------	-------

## Sensing ranges with GLL170T

Operating mode 50 µs	30 mm
Operating mode 250 µs	52 mm

## Dimensional drawing (Dimensions in mm (inch))

#### LL3-DC47



# LL3-DC47 | LL3

**FIBERS** 

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

# **WORLDWIDE PRESENCE:**

Contacts and other locations -www.sick.com

