

PRODUCT-DETAILS

SDA-F-1.1.1-WL

SDA-F-1.1.1-WL WL-Sensor/Dim act. 1/1g



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | SDA-F-1.1.1-WL |
| Code de produit | 2CKA006200A0077 |
| EAN | 4011395215661 |
| Description courte | SDA-F-1.1.1-WL WL-Sensor/Dim act. 1/1g |

Description longue

For dimming 230 V \sim loads. Communication with the free@home system is carried out wireless. With integrated universal dimming actuator for controlling LEDs, incandescent lamps, 230 V halogen lamps, low-voltage halogen lamps with conventional or electronic transformers, and dimmable energy-saving halogen lamps. For dimmable Retrofit-LEDs (LEDi). Dimming function is available also without prior programming (pre-configured). Configuration can be changed later via the web interface (groups, scenes, etc.). For contacting 1gang rocker 6230-10-xxx, 6231-10-xxx, 6232-10-xxx, 6233-10-xxx und 6234-10-xxx. 2-wire connection (neutral conductor not required) 3-wire connection technology is possible as an option for improved load behaviour (for details see the online operating manual). With 230 V extension unit input (dimming brighter/darker, switching). With fixing claws.

Installation

| | |
|-------------------------|--------------------|
| Instructions et manuels | No document needed |
|-------------------------|--------------------|

Technique

| | |
|--|-----------------|
| Fiche produit, informations techniques | 2CKA001473B9110 |
|--|-----------------|

| | |
|------------------------------------|---------------------------------|
| Tension nominale (U _r) | 230 V |
| Tension | 230...230 V |
| Auxiliary Voltage AC/DC | 230 V AC/DC |
| Fréquence assignée (f) | 50 ... 60 Hz |
| Nombre de sorties | 1 |
| Compatible Bus Systems | free@home |
| Product Range | free@home |
| Type de montage | Flush Mounted |
| Model Number | Dimming actuator |
| Nombre de batteries | 0 |
| Application Function | Data Communication / Multimedia |

Environnement

| | |
|---|-----------------------------------|
| Température de l'air ambiant | Operation -5 ... +45 °C |
| Indice de protection | IP20 |
| Statut RoHS | Following EU Directive 2011/65/EU |
| Informations RoHS | 2CKA200000E7841 |
| REACH Declaration | 2CKA309999E9999 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

Dimensions

| | |
|---|---------|
| Produit Largeur Net | 71 mm |
| Produit Hauteur Net | 71 mm |
| Produit Longueur Net | 34 mm |
| Poids net | 108.4 g |
| Profondeur d'encastrement (t ₂) | 32 mm |

Commande

| | |
|--------------------------------------|------------------------------------|
| ID Produit de remplacement (NOUVEAU) | 2CKA006500A0013 2CKA006200A0281 |
| ID du produit remplacé | 6200-0-0077 |

Certificats et Déclarations (Numéro de document)

| | |
|--------------------------------|-----------------|
| Déclaration de Conformité - CE | 2CKA100000E2642 |
|--------------------------------|-----------------|

Classifications

| | |
|----------------|--|
| ETIM 8 | EC001094 - Dimming actuator for bus system |
| ETIM 9 | EC001094 - Dimming actuator for bus system |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 8538 90 91 |

Catégories

Produits basse tension → Home and Building Automation → free@home → Lighting Control → Universal Dim Actuators

