




°C

max

+85

Product designation			Push-push button actuators
Product type designation			LPFQ20
General characteristics			
Colour			Blue
			Extended
Type of positions			pushbutton. Push
			on-push off Aluminium and
Material			zinc alloy
IEC degree of protection			IP66, IP67 and
			IP69K
Mechanical features			
Operating force		kg-lb	<0.5Kg / 1.1lb
Mechanical life - Push-Push actuators		cycles	500000
Fixing			Without mounting
			adapter
Mounting adapter			LPXAU120M
UL technical data			
UL degree of protection			Type1, 2, 3R, 4,
Ambient conditions			4X, 12, 12K
Temperature			
Operating temperature			
	min	°C	-25
	max	°C	+70
Storage temperature			
	min	°C	-40

## Dimensions



## Certifications and compliance

## Com

mpliance	
	CSA C22.2 n° 14
	IEC/EN/BS 60947-1
	IEC/EN/BS 60947-5-1
	UL508
rtificates	

Certificat	es	
	cULus	
ETIM clas	ssification	
LPFQ206	The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding	1 / 2

LPFQ206

PUSH-PUSH BUTTON ACTUATOR Ø30MM PLATINUM SERIES FLAT METAL, EXTENDED. PUSH ON-PUSH OFF, BLUE



ETIM 8.0

EC000221 -Front element for push button