

# STRIP LED

100932.99

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



## Features

Use: Indoor  
Dimming: WITH ACCESSORY  
Emergency: WITH ACCESSORY  
L: 5000mm  
A: 10mm  
Warranty: 5 years  
Weight: 0.15kg



## Tech data

Luminous flux in emergency: L min = 30 L max = 140 - 1h: 18% / 3h: 7%  
IP: 20  
Insulation class: III  
Supply voltage: 48 Vdc  
Energy efficiency class: E  
SELV: No

## Source

Light source: LED  
Source power: 17W/m  
Source luminous flux: 2096lm  
Colour temperature: 3000K  
CRI: >90  
LED lifespan: 30000h L70 B20

## Compliance


CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

## Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



SMD 2835 (240 LED/m)  
Biadesivo - sezionabile ogni 62,5 mm (15 LED)  
Biadesive - cuttable every 62,5 mm (15 LED)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.