

## LIGHT SOURCE

LED quantity	1
Power max	1 W – 2 W
Total lumen output (3000K)	14 lm - 19 lm
Efficacy lm/W (3000K)	14 lm/W – 10 lm/W
LOR (3000K)	13% - 12%
CRI	>80
LED Temperature (K)	2700-3000-4000-5000
Average operational life	50.000 hours

## OPTIC

Material	PMMA lens
Available optics	Single light emission, double light emission, triple light emission
Beam direction	Fixed
Flux symmetry	Asymmetrical
Accessories	-

## LED FIXTURE

Material	Aluminum – AISI 316L
Finish	Aluminum Hard Coat Anodizing(Black, Grey, Titanium), AISI 316L
Available finishes	Black, Grey, Titanium, Stainless steel
IP Rate	IP67
Working Temperature	-20° ÷ +40°
Accessories	-

## ELECTRICAL FEATURES

Driver	Remote
Dimmable	Push, 1-10V, DALI
For emergency lighting	-
Connection in	In series at 350mA-500mA, in parallel at 24Vdc
Class	III

## MECHANICAL FEATURES

Dimensions (mm)	Ø50 x 86
Weight	250 gr
Mounting	WII, floor recessed
Cut-out (mm)	-
Use	Outdoor

## NOTES

Recessed box recommended

