


21700541	<b>DATA SHEET</b>	
Valid from: 17.09.2018	<b>ED-PB-90-RP-PG</b>	

## Description

- PROFIBUS Sub-D plug with screw connector, 9-pole
- For cable diameters 5.0 – 8.0 mm
- Status LEDs
- Easy to connect
- Metallized housing



## General characteristics

Programming/diagnostic interface	Yes
Cable outlet	90°
Connection type	Screwing
Interfaces	PROFIBUS-station: SUB-D socket, 9-pole PROFIBUS-cable: 4 terminals for wires up to 1.0 mm <sup>2</sup> Protocol: PROFIBUS DP per EN
Suitable cable-Ø	5.0 – 8.0 mm
Termination resistor	Integrated, connectable with slide switch
Transmission rate (max.)	9.6 kbit/s to 12 Mbit/s
Temperature range	0 °C to +60 °C (32 °F to 140 °F) (operation) -25 °C to +75 °C (-13 °F to 167 °F) (storage/transportation)
Protection class	IP 20

## Mechanical characteristics

Dimensions	64 mm x 40 mm 17 mm (LxWxH)
Weight	Appr. 40 g

## Electrical characteristics

Pollution degree	2
Supply voltage	+5 V DC
Current consumption (typ.)	100 mA

## Application range

Automation, industrial machinery and plant engineering

## Note

Photographs are not true to scale and do not represent detailed images of the respective products.

Creator: MOKO2/PDP Released: IVSE1/PDP	Document: DB21700541EN Version: 03	Page 1 of 1
---	---------------------------------------	-------------