

PRODUCT-DETAILS

6817/62-183-500

Presence Detector 8 m 200 W



Informations générales

| | |
|------------------------------|-----------------------------|
| Extension du type de produit | 6817/62-183-500 |
| Code de produit | 2CKA006800A2771 |
| EAN | 4011395217955 |
| Description courte | Presence Detector 8 m 200 W |

| | |
|--------------------|---|
| Description longue | <p>Master presence detector with mixed light measurement. For switching lighting systems that depend on brightness and movement. With electronic switch contact for LED operation.</p> <p>Detection range (for installation height of 3 m): circular Seated persons: up to Ø 6.5 m, walking persons: up to Ø 8 m. Extension of the detection range by means of master/slave combination. Visible height 23 mm. For semiautomatic and fully automatic operation.</p> <p>Additional activation/deactivation possibility through pushbutton input. With continuous light/continuous off function (8 hours), activation via intelligent extension unit input possible.</p> <p>With brightness-independent test mode for evaluating the detection zone. With teach-in function of the brightness switching threshold, IR service remote control required. With detection display in test mode. Ceiling installation using integrated spring bracket. Twist protection via additional quick tensioning. Adjustment elements accessible on the front side.</p> <p>Surveillance density: 48 sectors with 496 switching segments. Switch-off delay: approx. 1 min. - 30 min. or short-time pulse adjustable. Remote control possible via IR service remote control 6843. Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm.</p> |
|--------------------|---|

Installation

| | |
|-------------------------|--------------------|
| Instructions et manuels | No document needed |
|-------------------------|--------------------|

Technique

| | |
|--|--|
| Fiche produit, informations techniques | 2CKA001673B9577 |
| Tension nominale (U _r) | 230 V AC |
| Auxiliary Voltage AC/DC | 110 V AC/DC 230 V AC/DC |
| Type de tension | AC |
| Current Range | Maximum 350 A |
| Fréquence (f) | 50...60 Hz |
| Fréquence assignée (f) | 50 / 60 Hz |
| Maximum Switching Power | 200 W |
| Power Loss | 0.3 W |
| Plage de mesure | 8 m |
| Nombre de sorties | 1 |
| Number of Switching Zones | 496 |
| Minimum Switching Time | Switch-On 60 second [unit of time] |
| Type de raccordement | Plug Clamp |
| Type de charge | 230 V incandescent lamps |
| Type de montage | Built-in |
| Sensor Type | Passive infrared |
| Finition de surface | Surface protection: Lacquered Surface finishing: Matt |
| Matériau | Thermoplastic |
| Type d'encastrement | Ceiling |
| Flux lumineux | 5 ... 2000 lx |
| Model Number | Presence detector |
| RAL Number | RAL 9006 - Aluminium blanc |
| Couleur | aluminium silver |
| Application Function | Electrical Load and Light Control |

Environnement

| | |
|---|--|
| Température de l'air ambiant | Operation -5 ... +45 °C |
| Indice de protection | IP40 |
| Statut RoHS | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Informations RoHS | 2CKA200000E6514 |
| REACH Declaration | 2CKA309999E9999 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

Dimensions

| | |
|---|---------|
| Produit Largeur Net | 94 mm |
| Produit Hauteur Net | 94 mm |
| Produit Longueur Net | 59 mm |
| Poids net | 146.9 g |
| Profondeur d'encastrement (t ₂) | 36 mm |

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité
- CE

2CKA100000E0706

Classifications

| | |
|----------------|--|
| ETIM 8 | EC000133 - Movement sensor complete |
| ETIM 9 | EC000133 - Movement sensor/presence detector complete |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 8536 50 80 |
| eClass | V11.0 : 27144007 |

Accessories

| Identifiant | Description | Type | Quantity | Unit Of Measure |
|-----------------|-------------------|----------------|----------|-----------------|
| 2CKA006800A2765 | Presence Detector | 6889/30-24-500 | 1 | piece |
| 2CKA006499A0002 | Extension Module | 6494-500 | 1 | piece |
| 2CKA006899A2304 | Protection Cover | 6898 | 1 | piece |

Catégories

Produits basse tension → Wiring Accessories - StandAlone Electronics → Presence Detector → Professional Series

