



## Features

Use: Indoor  
Type of installation: RECESSED INTO BRICKWORK, RECESSED INTO PLASTERBOARD  
Emission: DIRECT  
Optics: TRANSPARENT  
Colour: WHITE  
Dimming: ON/OFF  
Emergency: NO  
L: 37mm  
A: 37mm  
H: 34mm  
D: 32-35mm  
Warranty: 5 years  
Weight: 0.12kg

## Tech data

Luminaire luminous flux: 110lm  
IP: 65  
Insulation class: III  
Supply voltage: DC 700 MA

## Source

Light source: LED  
Source power: 2W  
Colour temperature: 3000K  
LED lifespan: 30000h L70 B20


## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)



## MOUNTING ACCESSORIES

---




NEWSTEP: PLACCA MURALE

**109405.99**


## ELECTRICAL ACCESSORIES

---




ALIM. LED 700MA - 30W - IP20

**E907K0030KK**




ALIM. LED 350MA - 8W - IP20

**E903K0006KK**




ALIM. LED 700MA - 12W - IP20

**E907K0012KK**



ALIM. LED 350MA - 15W - IP20

**E903K0015KK**



ALIM. LED 4W/700MA 2.5-6V

**101322.99**


# NEWSTEP

109401.01

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948

## DIMMABLE ACCESSORIES

---



ALIM. LED 25W 700MA/2-36V DALI/PUSH

**101336.99**



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.