

## Features

Use: Indoor  
 Type of installation: RECESSED INTO PLASTERBOARD  
 Emission: DIRECT  
 Optics: SPOT  
 Beam: 36°  
 Colour: WHITE  
 Dimming: WITH ACCESSORY  
 Emergency: WITH ACCESSORY  
 A: Ø80mm  
 H: 121mm  
 D: 70mm  
 Warranty: 5 years  
 Weight: 0.45kg

## Tech data

Luminaire luminous flux: 1590lm  
 Luminous flux in emergency: 1h: 23% / 3h: 9%  
 IP: 20  
 Insulation class: III  
 Supply voltage: DC 500 mA  
 SELV: No

## Source

Light source: LED  
 Source power: 18W  
 Colour temperature: 3000K  
 CRI: >90  
 LED lifespan: 30000h L70 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

## Standards


Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

## ELECTRICAL ACCESSORIES


---



ALIM. LED MAX 18W 500MA

**101325.99**

---




ALIM. LED MAX 20W 500MA

**101309.99**

---

## DIMMABLE ACCESSORIES


---



ALIM. MAX.20W/500MA DALI/PUSH/0-10/1-10

**101904.99**

---




ALIM. LED 25W 500MA/2-50V DALI/PUSH

**101334.99**

---

## EMERGENCY ACCESSORIES


---



KIT EMERGENZA 3H 10V-54V

**18005.99**

---



KIT EMERGENZA 1H 10V-54V

**18004.99**

---