

AU-X7

LUMINAIRES - ÉCLAIRAGE ENCASTRÉ COUPE-FEU


Product Description:


Product Image:



Polar Curve







Product Specs:

Technology	LED	Input Voltage	220-240V AC	
Positional Adjustment	Fixe	Number of LEDs	14	
Luminaire Distribution	Direct	Lifetime L70 (hrs)	35000	
Input Frequency	50/50HZ	Dimmable	Oui	
Dali	Non	IP Rating	IP65	
Fire Protection	Oui	Acoustic Rated	Oui	
Operating Env. Temp. (Min) °C	-20°C	Operating Env. Temp. (Max) °C	25°C	
Optic Material	Polycarbonate	Power Factor	0.9	
Overall Diameter (mm)	88	Height (mm)	58	
Recess Depth (mm)	58	Cutout Diameter (mm)	70	
Weight (Kg)	0.181			

SKU Table and Ordering:

SKU Code	Wattage	Beam Angle	Lumens	Lumens/Watt	Colour	Finish Colour
AU-X7/30	7	60	580	83	3000	Blanc
AU-X7/40	7	60	620	89	4000	Blanc

Compliance & Approvals:



Warranty:

This product has a guarantee period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

UK Head Office

Apex Park 6 Little Burrow Welwyn Garden City AL7 4SW United Kingdom Tel : +44 (0) 1707 228 700