

PRODUCT-DETAILS

# P9B10VN

## P9B10VN Contact Block



### Informations générales

Extension du type de produit	P9B10VN
Code de produit	1SFA187002R8001
EAN	7320500522868
Description courte	P9B10VN Contact Block
Description longue	The P9B10VN Contact Block is: Modular metal - Contact Block - Brown - Front mounting - 1 NO This Contact Block is part of ABB's modular metal range designed for mining, construction and heavy industry applications, combining the highest reliability with the full flexibility of a modular range.

### Commande

Quantité minimum	10 pièce
Code douanier	8536901000

### Downloads Préférés

Fiche produit, informations techniques	1SFC151007C02_
Instructions et manuels	1SFC151011M0201

## Dimensions

Produit Largeur Net	9.6 mm
Produit Hauteur Net	39.5 mm
Produit Longueur Net	27.7 mm
Poids net	0.05 kg

## Technique

Température de l'air ambiant	Operation -30 ... 70 °C Storage -40 ... +70 °C
Couleur	Brown
Type de montage	Front mounting
Number of Auxiliary Contacts NO	1
Indice de protection	Terminals IP20
Degré de pollution	3
Tension assignée d'isolement (U <sub>i</sub> )	690 V
Tension assignée de tenue aux chocs (U <sub>imp</sub> )	4 kV
Connecting Capacity	Flexible with Ferrule 1 x 0.75...2.5 mm <sup>2</sup> Flexible with Ferrule 2 x 0.75...2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1 x 0.75...2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2 x 0.75...2.5 mm <sup>2</sup> Flexible 1 x 0.75 ... 2.5 mm <sup>2</sup> Flexible 2 x 0.75 ... 2.5 mm <sup>2</sup> Solid 1 x 0.75...2.5 mm <sup>2</sup> Solid 2 x 0.75...2.5 mm <sup>2</sup>
Type de raccordement	Screw Clamp
Type de borne	Screw Terminals
Couple de serrage	0.9 N·m
Wire Stripping Length	10 mm

## Technique UL/CSA

Connecting Capacity	1x 18...14 AWG
UL/CSA	2x 18...14 AWG

## Environnement

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2022-006479
Informations RoHS	2CMT2019-005862
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
WEEE B2C / B2B	Business To Business
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)

---

**Certificats et Déclarations (Numéro de document)**


---

Certificat BV	2CMT2019-005867
CB Certificate	2CMT2019-005873
CQC Certificate	CQC2013010304650811
Certificat CSA	2CMT2019-005868
Certificat ecULus	2CMT2019-005868
Declaration of Conformity - CCC	2020980304001860
Déclaration de Conformité - CE	2CMT2019-005862
Declaration of Conformity - UKCA	2CMT2020-006121
DNV GL Certificate	2CMT2019-005876
Certificat RINA	2CMT2019-005866
Certificat UL	2CMT2019-005868

---



---

**Emballage**


---

Emballage Niveau 1 Unités	bag 1 pièce
Emballage Niveau 1 Largeur	80 mm
Emballage Niveau 1 Longueur	50 mm
Emballage Niveau 1 Hauteur	120 mm
Emballage Niveau 1 Poids	0.05 kg
Emballage Niveau 1 EAN	7320500522868

---



---

**Classifications**


---

ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
eClass	V11.0 : 27371302
UNSPSC	39122221
Code de catégorie granulaire IDEA (IGCC)	5219 >> Switch part or accessory
E-Number (Finland)	2313795
E-Number (Sweden)	3705930

---



---

**Catégories**


---

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Unités de commande et de signalisation → Modular Metal Range P9M

