

PRODUCT-DETAILS

6725-500

WaveLine Flush Mounted Inserts 230 V



Informations générales

Extension du type de produit	6725-500
Code de produit	2CKA006720A0008
EAN	4011395182710
Description courte	WaveLine Flush Mounted Inserts 230 V

Description longue

Radio control telegrams are sent when the two extension units are activated with mains voltage (AC 230 V~). Operation via conventional push button (2020 US/2021/6 UK) possible. The 2gang binary input has 5 function modes: 1.) 2-channel switching: Connection of conventional push buttons. Alternately sends ON/OFF telegrams when actuated. 2.) 2-channel dimming: Connection of conventional push buttons. Sends dimming telegrams when actuated. 3.) 1 channel blind: Connection of a 2gang push-button or blind control insert II. Sends telegrams to control a blind when actuated (only movement command, no stop. 4.) Two-channel light scene control: Connection of conventional push-buttons. Light scenes are stored and started when actuated. 5.) Channel 1: Switching ON. Channel 2: Continuous switching ON/OFF: At >Switching ON< an ON telegram is sent with a brief actuation. At >Continuous switching< ON/OFF and actuated extension unit, an ON telegram is sent every minute, and an OFF telegram is sent every minute for a non-actuated extension unit. In dependence of the selected function, it can be combined with WaveLINE actuators 6701-101, 6702, 6703, 6704, 6705-101. Repeater function can be activated for extended range. For universal attachment or installation. Phase and neutral conductor required. For installation in (deep) flush-mounted boxes to German Standard DIN 49073. Send/receive frequency: 868 MHz. Free-field range: approx. 100 m.

Installation

Technique

Fiche produit, informations techniques	No document needed
Tension nominale (U _r)	230 V
Auxiliary Voltage AC/DC	230 V AC/DC
Fréquence assignée (f)	50 Hz
Number of Channels	2
Conception	WaveLine
Product Range	WaveLINE
Norme de transmission	Radio Control
Type de montage	Flush Mounted
Finition de surface	Surface protection: Untreated Surface finishing: Matt
Matériau	Plastic Thermoplastic
RAL Number	RAL 9016 - Blanc signalisation
Couleur	studio white
Poids de la batterie	0 g
Longueur du câble	0.11 m
Application Function	Electrical Load and Light Control Blind / Shutter / Shading Control

Environnement

Température de l'air ambiant	Operation -5 ... +45 °C
Indice de protection	IP20
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations RoHS	2CKA200000E6210
REACH Declaration	2CKA309999E9999
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Poids net	66 g
Profondeur d'encastrement (t ₂)	15 mm

Commande

ID du produit remplacé	6720-0-0008
------------------------	-------------

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CKA100000E1798
-----------------------------------	-----------------

Classifications

ETIM 8	EC000257 - Transmitter/Remote control for domestic switching devices
ETIM 9	EC000257 - Transmitter/Remote control for domestic switching devices
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8517 62 00
eClass	V11.0 : 27144039

Accessories

Identifiant	Description	Type	Quantity	Unit Of Measure
2CKA006700A0023	WaveLine Flush Mounted Inserts 1 gang(s) 230 V	6702-500	1	piece
2CKA006700A0025	RF-Dimmer Actuator 1 gang(s) 230 V	6704-500	1	piece
2CKA006700A0042	Flush Mounted Inserts 2 gang(s) 230 V	6705-101-500	1	piece

Catégories

Produits basse tension → Wiring Accessories - Light Switch Ranges → Flush Mounted Inserts → Electronic Inserts

