

### Features

Use: Indoor  
Type of installation: RECESSED INTO PLASTERBOARD  
Emission: DIRECT  
Optics: OPAL  
Beam: 100°  
Colour: WHITE  
Dimming: WITH ACCESSORY  
Emergency: WITH ACCESSORY  
A: Ø125mm  
H: 25mm  
D: 110mm  
Warranty: 5 years  
Weight: 0.35kg

### Tech data

Luminaire input power: 11W  
Luminaire luminous flux: 950lm  
Luminous flux in emergency: 1h: 53% / 3h: 21%  
IP: 40  
Insulation class: II  
Supply voltage: 220-240V 50/60Hz  
SELV: Si

### Source

Light source: LED  
Source power: 9W  
Source luminous flux: 1120lm  
Colour temperature: 3000K  
CRI: >90  
LED lifespan: 50000h L80 B20

### Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2


### Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

## DIMMABLE ACCESSORIES


---



ALIM. LED 25W 350MA/2-50V DALI/PUSH

**101333.99**

---




ALIM. LED DALI/PUSH 21W/350MA 20-60V

**101323.99**

---

## EMERGENCY ACCESSORIES


---



KIT EMERGENZA 3H 10V-54V

**18005.99**

---



KIT EMERGENZA 1H 10V-54V

**18004.99**

---