

Product Specifications

1. Designation:	LR6 / SUM-3 / ALKALINE AA SIZE
2 Kind of products specified:	Alkaline-Manganese dry cell battery
3. Nominal Voltage:	1.5V
4. Dimensions:	$49.8{\pm}0.6mm\times \texttt{ø14}{\pm}0.5$
5. Approximate Weight:	23g
6. Appearance:	There is not stain, scratch, nor deformation which will
	cause trouble in practical use is observed.
7. Terminal:	Standard snap fastener stud (+) and socket (-)
8. Jacket:	Foil Jacket

9. Electrolyte-Leakage resistance:

After testing by Table 1, shall be no leakage and deformation by visual inspection.

Table 1

ITEM	CONDITIONS			
	Temperature	Relative Humidity	Load Resisto	Term
Overdischarge electrolyte leakage	20.7±1.3°C	$55~\pm~8\%$	10 Ω	48hrs

10. Mercury content

Test condition	Standard demand	Test results	Judgement
Atomic absorption spectrophotometric method	≤ 1×10-4%	≤ 8×10-6%	qualified

11. Markings on product:

- (1). Battery type: LR6-----Best Quality
- (2). Brand: Microbatt
- (3). Polarity: "+" and "-"
- (4). Other specified markings

12. Output Service	Load Resistance	3.9Ω	10 Ω 4	3Ω
	Discharge Method	24h/d	24h/d	4h/d
	End-Point Voltage.	0.9V	0.9V	0.9V
	Stand Stadus	320min	12h	60h
	Actual Performance	350min	18.5h	90h

- **13. Packing:**The battery shall be packed so as not likely to be demaged
during transportation and storge
- 14. Warranty: Within 60 months after delivery