

PRODUCT-DETAILS

CM-ENS.13S

CM-ENS.13S Liquid level monitoring relay 1c/o, sensitivity 5-100kOhm



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | CM-ENS.13S |
| Code de produit | 1SVR730850R2100 |
| EAN | 4013614502903 |
| Description courte | CM-ENS.13S Liquid level monitoring relay 1c/o, sensitivity 5-100kOhm |

| | |
|--------------------|--|
| Description longue | <p>The CM-ENS.13S belongs to the CM liquid level monitoring relay range. It operates with a rated control supply voltage of 110-130 V AC and 220-240 V AC and has a 1 c/o (SPDT) output with contacts rated at 250 V / 4 A. It monitors liquid levels of conductive fluids and protects pumps against dry running or tanks against overflow and works according to the open-circuit principle. The sensitivity can be selected via front-face potentiometers. Several electrodes and a sealable transparent cover for protection against unauthorized changes are available as accessory. The device offers screw connection technology with double-chamber cage connection terminals.</p> |
|--------------------|--|

Commande

| | |
|------------------|---------------|
| EAN | 4013614502903 |
| Quantité minimum | 1 pièce |
| Code douanier | 85364900 |

Downloads Préférés

| | |
|--|------------------------------------|
| Fiche produit, informations techniques | 2CDC112228D0201 |
| Instructions et manuels | 1SVC730680M1001 1SVC730680M0001 |
| CAD Dimensional Drawing | 2CDC001079B0201 |

Dimensions

| | |
|----------------------|----------|
| Produit Largeur Net | 22.5 mm |
| Produit Hauteur Net | 85.6 mm |
| Produit Longueur Net | 103.7 mm |
| Poids net | 0.153 kg |

Technique

| | |
|---|--|
| Fonction | Filling or draining monitoring |
| Number of Electrodes | 3 |
| Plage de mesure | 5 ... 100 k Ω |
| Rated Control Supply Voltage (U_g) | 110 ... 130 V AC 220 ... 240 V AC |
| Fréquence assignée (f) | Supply Circuit 50/60 Hz |
| Sortie | 1 c/o (SPDT) contact |
| Type de borne | Screw Terminals |
| Rated Operational Current AC-12 (I_{θ}) | (230 V) 4 A |
| Courant assignée d'emploi AC-15 (I_{θ}) | (230 V) 3 A |
| Rated Operational Current DC-12 (I_{θ}) | (24 V) 4 A |
| Courant assignée d'emploi DC-13 (I_{θ}) | (24 V) 2 A |
| Minimum Switching Capacity | 12 V 10 mA |
| Tension assignée de tenue aux chocs (U_{imp}) | Measuring Circuit / Output Circuit 4 kV Output Circuit 1 / Output Circuit 2 4 kV Supply Circuit / Measuring Circuit 4 kV Supply Circuit / Output Circuit 4 kV |
| Tension assignée d'isolement (U_i) | Measuring Circuit / Output Circuit 300 V Output Circuit 1 / Output Circuit 2 300 V Supply Circuit / Measuring Circuit 300 V Supply Circuit / Output Circuit 300 V |
| Indice de protection | Housing IP50 Terminals IP20 |
| Catégorie de Surtension | III |
| Degré de pollution | 3 |
| Dispositif de protection contre les courts-circuits | Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A |
| Electrical Durability | AC-12 100000 cycle |
| Durabilite mecanique | 1000000 cycle |
| Connecting Capacity | Flexible with Ferrule 1x 0.5 ... 2.5 mm ² |

| | |
|--------------------------|--|
| | Flexible with Ferrule 2x 0.5 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.5 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm ² Flexible 1x 0.5 ... 2.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 1x 0.5 ... 4 mm ² Rigid 2x 0.5 ... 2.5 mm ² |
| Couple de serrage | 0.6 ... 0.8 N·m Control Circuit 0.9 N·m Main Circuit 1 N·m |
| Wire Stripping Length | 8 mm Main Circuit 10 mm |
| Recommended Screw Driver | 0.8 x 4 4.5 Pozidriv 1 |
| Type d'encastrement | 1 ... 5 1 ... 6 |
| Montage sur rail DIN | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 |
| Normes et standards | CAN/CSA C22.2 No.14 IEC/EN 63000 IEC/EN 60255-27 IEC/EN 61000-6-2 IEC/EN 61000-6-3 UL 508 |

Technique UL/CSA

| | |
|----------------------------------|--|
| Maximum Operating Voltage UL/CSA | Output Circuit 300 V AC |
| Contact Rating UL/CSA | B300 |
| Connecting Capacity UL/CSA | Flexible 1x 18-14 AWG Flexible 2x 18-16 AWG Rigid 1x 20-12 AWG Rigid 2x 20-14 AWG |
| Tightening Torque UL/CSA | 7.08 in·lb |
| Pilot Duty UL/CSA | B300 |

Environnement

| | |
|---|--|
| Température de l'air ambiant | Operation -25 ... +60 °C Storage -40 ... +85 °C |
| Altitude de fonctionnement maximale autorisée | Without Derating 2000 m |
| REACH Declaration | 1SVD981001-4501 |
| Informations RoHS | 1SVD981005-00 |
| Statut RoHS | Following EU Directive 2011/65/EU |

Valeur Circulaire

| | |
|--|-----------------|
| Instructions relatives à la fin de vie | 1SAC200290H0001 |
|--|-----------------|

Certificats et Déclarations (Numéro de document)

| | |
|-------------------------------------|---------------------------|
| CQC Certificate | CQC2015010303819793 |
| Certificat ecULus | cULus508_20150627-E140448 |
| Declaration of Conformity - CCC | 2020980303000198 |
| Déclaration de Conformité - CE | 1SVD981005-00 |
| Declaration of Conformity - UKCA | 1SVD981005-10 |
| DNV GL Certificate | DNV_GL_TAA00000RW |
| EAC Certificate | EAC_RU_C-DE.ME77.B.02330 |

Emballage

| | |
|--------------------------------|---------------|
| Emballage Niveau 1 Unités | box 1 pièce |
| Emballage Niveau 1 Largeur | 97 mm |
| Emballage Niveau 1 Longueur | 30 mm |
| Emballage Niveau 1 Hauteur | 109 mm |
| Emballage Niveau 1 Poids | 0.177 kg |
| Emballage Niveau 1 EAN | 4013614502903 |

Classifications

| | |
|-----------------------------------|--|
| Code de classification d'objet | B |
| ETIM 7 | EC001447 - (Fill) level monitoring relay |
| ETIM 8 | EC001447 - (Fill) level monitoring relay |
| ETIM 9 | EC001447 - (Fill) level monitoring relay |
| eClass | V11.0 : 27371813 |
| UNSPSC | 39122331 |
| E-Number (Finland) | 2712569 |

Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Relais électroniques → Contrôle et réglage des niveaux de liquide → CM-Enx

