



Hauteur de 6 à 8 mètres
6 to 8 meters height

Fût octo-conique en acier. 60 mm en tête, 2 rangées de crevés taraudés à 100 et 200 mm du sommet.

Octagonal conical steel pole. 60 mm top dia, 2 rows of threaded holes at 100 and 200 mm from top.



Dimensions

HS m	Øa mm	Øb mm	Lp mm	Pp mm	Hp mm	Cxd mm	E mm	J TS mm
6	60	156	500	95	600	80x105	300	J 20/18x400
7	60	156	500	95	600	80x105	300	J 20/18x400
8	60	156	500	95	600	80x110	300	J 20/18x400

Capacités

HS m	Kg	22 m/s		24 m/s		26 m/s		28 m/s		34 m/s		M m.daN	T daN	Lm x Hm m
		Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I			
6	50	1,12	0,88	0,89	0,70	0,72	0,56	0,59	0,44	0,31	0,22	779	226	0.6x0.7
7	50	0,78	0,59	0,60	0,45	0,46	0,34	0,36	0,25	0,15	0,07	795	222	0.6x0.7
8	50	0,52	0,37	0,38	0,26	0,27	0,17	0,18	0,10	-	-	788	187	0.6x0.7



Luminaire PHILIPS

Accessoires et options
PORTE



Accessoires et options
PIED DE MÂT

