



Product designation			Current trasformers
Product type designation			DM35T0600
Auxiliary supply Us			
Operational frequency			
	min	Hz	50
	max	Hz	60
Current inputs			
Primary current Ipn (/5)		А	600
Secondary output current		А	5
Overload withstand Ipn		%	120
Insulations			
Rated insulation voltage Ui IEC/EN		V	720
IEC rated short-time thermal current Ith		Ith for s	4060
IEC rated dynamic current Idyn		Ith for s	2.5
Insulation dry type			Class E
Mechanical features			
Terminals type			Screw
Fixing			DIN rail or by Screw
Ambient conditions			
Temperature			
Operating temperature			
	min	°C	-25
	max	°C	+50
Storage temperature			
	min	°C	-40
	max	°C	+80
Relative humidity		%	90
Protection degree			IP30
Dimensions			

DM35T0600



CURRENT TRANSFORMER, SOLID-CORE, FOR Ø66MM CABLE. FOR 80X12.5MM, 60X30MM, 50X50MM BUSBARS, 600A

Ø66 (2.60") -51.5 (2.03") -61.5 (2.42") 126.5 (4.98") E 31.5 (1.24") -20-41.5 -51.5 (2.03") (0.79")(1.63")61.5 (2.42") 81.5 (3.21") - 105 (4.13") Certifications and compliance Compliance IEC/EN/BS 61869-1 IEC/EN/BS 61869-2 Certificates EAC ETIM classification EC002048 -

ETIM 8.0

EC002048 -Current transformer