

Power supply 1.5m for RA-/C3A



Part no. RA-C4-PPB/C3-1M5
116962

Product name	Eaton Moeller® series Rapid Link Accessory Power connection cable
Part no.	RA-C4-PPB/C3-1M5
EAN	4015081167029
Product Length/Depth	1.5 metre
Product height	300 millimetre
Product width	300 millimetre
Product weight	0.55 kilogram
Compliances	CE
Product Tradename	Rapid Link
Product Type	Accessory
Product Sub Type	Power connection cable
Color	Gray
Features	Oil resistant (acc. EN 60811-404) Connector system system-oriented
Fitted with:	Protective conductor
Functions	For connecting the device with the round cable junction
Degree of protection	Other
Nominal current	6.6 A
Nominal voltage - min	380 V
Nominal voltage - max	480 V
Product category	Power supply
Permissible ambient temperature - min	-10 °C
Permissible ambient temperature - max	55 °C
Cable type	5 x 1.5 mm ² , halogen-free, with RA-C4-PPB plug for round cable junction, power plug and gasket IP65
Outer diameter - approximate	10 mm
Outer sheath material	Other

Technical data ETIM 8.0

Batteries, chargers and power cords (EG000053) / Power cord (EC001576)		
Electric engineering, automation, process control engineering / Cable, wire / Ready-made low-voltage line / Extension line (low-voltage line) (ec!@ss10.0.1-27-06-04-02 [AAB665013])		
Connection 1		Other
Connection 2		Other
Connector system system-oriented		Yes
Number of cores		5
Nominal cross section conductor	mm ²	1.5
Length	m	1.5
Material outer sheath		Other
Temperature resistance	°C	-10 - 55
Nominal current	A	6.6
Nominal voltage	V	380 - 480
Frequency	Hz	50 - 60
Colour outer sheath		Grey
Spiralized cable		No
With protective conductor		Yes

Degree of protection (IP)			Other
Oil resistant (according to EN 60811-404)			Yes
With cord switch			No
Outer diameter approx.		mm	10
Reaction-to-fire class according to EN 13501-6			None
Smoke development class according to EN 13501-6			None
Euro class flaming droplets/particles according to EN 13501-6			None
Euro class acidity according to EN 13501-6			None