

PRODUCT-DETAILS

6800-22G-104M

Electronic Controls Movement sensor ivory



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | 6800-22G-104M |
| Code de produit | 2CKA006800A2086 |
| EAN | 4011395990988 |
| Description courte | Electronic Controls Movement sensor ivory |
| Description longue | For automatic switching of devices dependent on motion and brightness. For down-to-ground detection. For relay inserts 6401 U-102, 6402 U and 6812 U-101. For MOS-Fet insert 6804 U-101. For Dimmer insert 6593 U. For extension insert 6805 U. With integrated selector switch for ON-AUTOMATIC-OFF (lockable). Soft phase-out: In combination with the 6593 U (mode of operation: Soft OFF) the illumination is dimmed down within 60 sec and switched off. Surveillance density: 28 sectors with 112 switching segments. Switch-off delay: 10 sec to 30 min or short-time pulse 1 sec adjustable. |

Installation

| | |
|-------------------------|-----------------|
| Instructions et manuels | 2CKA001373B7858 |
|-------------------------|-----------------|

Technique

| | |
|-------------|---|
| Adapté pour | 2CKA006401A0048 2CKA006401A0047 2CKA006401A0050 2CKA006590A0156 2CKA006590A0169 2CKA006800A1468 2CKA006800A2011 |
|-------------|---|

| | |
|------------------------|------------------------------------|
| Minimum Switching Time | Switch-On 10 second [unit of time] |
| Type de montage | Flush Mounted |
| Matériau | Thermoplastic |
| Model Number | Movement sensor |
| RAL Number | RAL 1013 - Blanc perlé |
| Couleur | ivory |
| Poids de la batterie | 0 g |

Environnement

| | |
|------------------------------|--|
| Température de l'air ambiant | Operation 0 ... +35 °C |
| Indice de protection | IP20 |
| Statut RoHS | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Informations RoHS | 2CKA200000E6328 |
| REACH Declaration | 2CKA309999E9999 |

Dimensions

| | |
|----------------------|-----------------|
| Produit Largeur Net | 70 mm |
| Produit Hauteur Net | 54 mm |
| Produit Longueur Net | 39 mm |
| Poids net | 0.03 kg |
| Schéma dimensionnel | 2CKA000097E0690 |

Commande

| | |
|------------------------|-------------|
| ID du produit remplacé | 6800-0-2086 |
|------------------------|-------------|

Certificats et Déclarations (Numéro de document)

| | |
|--------------------------------|-----------------|
| Déclaration de Conformité - CE | 2CKA100000E1883 |
|--------------------------------|-----------------|

Classifications

| | |
|----------------|--|
| ETIM 8 | EC000138 - Sensor element for movement sensor |
| ETIM 9 | EC000138 - Sensor element for movement sensor |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 8538 90 99 |
| eClass | V11.0 : 27144008 |

Accessories

| Identifier | Description | Type | Quantity | Unit Of Measure |
|-----------------|-----------------------------|----------------|----------|-----------------|
| 2CKA006401A0047 | Flush Mounted Inserts 230 V | 6402 U | 1 | piece |
| 2CKA006590A0156 | Flush Mounted Inserts 127 V | 6590 U-127-500 | 1 | piece |
| 2CKA006800A1468 | Flush Mounted Inserts 230 V | 6805 U | 1 | piece |
| 2CKA006800A2011 | Flush Mounted Inserts 230 V | 6812 U-101 | 1 | piece |

Catégories

Produits basse tension → Wiring Accessories - Light Switch Ranges → Cover Plates and Control Elements → Electronic Controls

