

PRODUCT-DETAILS

OT630KFCC3BA

OT630KFCC3BA Encl. Switch Disconnecter



Informations générales

| | |
|------------------------------|---|
| Extension du type de produit | OT630KFCC3BA |
| Code de produit | 1SCA022834R0370 |
| EAN | 6417019289403 |
| Description courte | OT630KFCC3BA Encl. Switch Disconnecter |
| Description longue | Encl. Switch Disconnecter, 3-p. 415V AC23 570A, 315kW. Plastic enclosure. IP65. RedYellow Pistol handle. Interlocked cover. Defeatable interlocking. The enclosure in the OT series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries knock out types for II-flanges. Cables can be inserted from top and bottom. The handle is padlockable and made for three padlocks. The cover is interlocked. The interlocking can be defeated. N and PE terminals included. |

Valeur Circulaire

| | |
|---|-----------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 1SCC340076D0201 |
| Informations RoHS | 1SCC340075D0201 |
| Toxic Substances Control Act - TSCA | 1SCC340095D0201 |

Commande

| | |
|------------------|--------------|
| Quantité minimum | 1 pièce |
| Code douanier | 85363090 |
| Pays d'origine | Finland (FI) |

Downloads Préférés

| | |
|--|--------------------|
| Fiche produit, informations techniques | 1SCC340015C0201 |
| Instructions et manuels | 1SCC340015M0004 |
| Mechanical Drawings | OTPK765625P2II.stp |

Dimensions

| | |
|----------------------|----------|
| Produit Largeur Net | 560 mm |
| Produit Hauteur Net | 760 mm |
| Produit Longueur Net | 250 mm |
| Poids net | 17.83 kg |

Technique

| | |
|---|---|
| Rated Operational Current AC-22A (I_e) | (380 ... 415 V) 570 A (690 V) 570 A |
| Rated Operational Current AC-23A (I_e) | (380 ... 415 V) 570 A (500 V) 570 A (690 V) 570 A |
| Rated Operational Power AC-23A (P_e) | (380 ... 415 V) 315 kW (500 V) 400 kW (690 V) 560 kW |
| Conventional Thermal Current (I_{the}) | Fully Enclosed 570 A |
| Tension assignée d'isolement (U_i) | acc. to IEC/EN 60664-1 1000 V |
| Tension | Circuit principal 1000 V |
| Rated Short-Circuit Making Capacity (I_{cm}) | (1000 V AC) 80 kA |
| Courant assigné de courte durée admissible (I_{cw}) | for 1 s 20 kA |
| Rated Conditional Short-Circuit Current (I_{nc}) | 90 kA |
| Power Loss | at Rated Operating Conditions per Pole 25 W |
| Degré de pollution | 3 |
| Handle Color | Red / Yellow |
| Handle Type | Pistol handle |
| Normes et standards | IEC 60947-1, -3 |
| Nombre de pôles | 3 |
| Neutral Type | Detachable neutral |
| Connecting Capacity Main Circuit | Hole Diameter 12 mm Screw Clamp / PE Terminal 4pc,25 ... 120 mm ² |
| Cable Entry Position | Top/Bottom |
| Cable Outlets Per Side | 2xII-flange / 2xII-flange |
| Indice de protection | acc. to IEC 60529 IP65 |
| Résistance aux chocs | Housing IK08 |
| Matériau du boîtier | Plastic |
| Maximum Mounted | 2 NO, 2 NC |

Auxiliary Contacts

| | |
|---------------------------------|---------------------|
| Mounted Auxiliary Contacts | 0 NO, 0 NC |
| Number of Auxiliary Contacts NC | 0 |
| Number of Auxiliary Contacts NO | 0 |
| Couple de serrage | Main Circuit 75 N·m |

Technique UL/CSA

| | |
|-------------------|---------------------|
| Couple de serrage | Main Circuit 75 N·m |
|-------------------|---------------------|

Environnement

| | |
|-------------------------------------|-----------------------------------|
| Statut RoHS | Following EU Directive 2011/65/EU |
| Toxic Substances Control Act - TSCA | 1SCC340095D0201 |

Certificats et Déclarations (Numéro de document)

| | |
|--------------------------------|-----------------|
| Déclaration de Conformité - CE | 1SCC340029D2704 |
| REACH Declaration | 1SCC340076D0201 |

Emballage

| | |
|-----------------------------|---------------|
| Emballage Niveau 1 Unités | box 1 pièce |
| Emballage Niveau 1 Largeur | 575 mm |
| Emballage Niveau 1 Longueur | 780 mm |
| Emballage Niveau 1 Hauteur | 340 mm |
| Emballage Niveau 1 Poids | 20 kg |
| Emballage Niveau 1 EAN | 6417019289403 |

Classifications

| | |
|--------------------------------|---|
| Code de classification d'objet | Q |
| ETIM 7 | EC000216 - Switch disconnecter |
| ETIM 8 | EC000216 - Switch disconnecter |
| ETIM 9 | EC000216 - Switch disconnecter (low voltage) |
| eClass | V11.1 : 27371403 |
| Catégorie DEEE | 4. Large Equipment (Any External Dimension More Than 50 cm) |

Catégories

Produits basse tension → Interrupteurs et appareillage à fusibles en coffret → Interrupteurs-sectionneurs en coffret → Enclosed Switch-Disconnectors

