

Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: LENS UGR<19
Colour: WHITE
Dimming: PUSH, DALI
Emergency: WITH ACCESSORY
L: 1125mm
A: 295mm
H: 14 (35 con alim.)mm
Warranty: 5 years
Weight: 4.0kg

Tech data

Luminaire input power: 56W
Luminaire luminous flux: 6832lm
Luminous flux in emergency: 11%
IP: 40
Insulation class: I
Supply voltage: 1500 mA ALIMENT.INCLUSO
UGR: <19
SELV: Si

Source

Light source: LED
Source power: 50W
Source luminous flux: 8359lm
Colour temperature: 4000K
CRI: >90
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

Standards


Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).


[View more product info](#)

MOUNTING ACCESSORIES




SCHOOL: KIT INST.PLAFONE 1200X300

104109.01




SCHOOL: KIT MOLLE PER INCASSO

104107.99




SCHOOL: KIT SOSPENSIONE H1200

104110.99



KIT ALIMENTAZIONE L1200 5P BIA

108921.01



THE PANEL 2: KIT INST.INC.RAS.CART.1200

102029.99



SCHOOL: KIT ANTICADUTA L=3000

104119.99