



Features

Use: Indoor
 Type of installation: RECESSED INTO PLASTERBOARD
 Emission: DIRECT
 Optics: SPOT
 Beam: 36°
 Colour: BLACK
 Dimming: WITH ACCESSORY
 Emergency: WITH ACCESSORY
 A: Ø65mm
 H: 105mm
 D: 60mm
 Warranty: 5 years
 Weight: 0.315kg

Tech data

Luminaire luminous flux: 592lm
 Luminous flux in emergency: 1h: 44% / 3h: 18%
 IP: 20
 Insulation class: III
 Supply voltage: DC 500 mA
 UGR: <19
 SELV: No

Source

Light source: LED
 Source power: 10W
 Source luminous flux: 945lm
 Colour temperature: 3000K
 CRI: >90
 LED lifespan: 30000h L70 B20

Compliance



CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

Standards


Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)




ELECTRICAL ACCESSORIES



ALIM. LED MAX 18W 500MA


101325.99



ALIM. LED 15W/500MA


101307.99

DIMMABLE ACCESSORIES




ALIM. MAX.20W/500MA DALI/PUSH/0-10/1-10

101904.99



ALIM. LED MAX 10W 500MA DALI PUSH


101316.99



ALIM. LED 25W 500MA/2-50V DALI/PUSH

101334.99

EMERGENCY ACCESSORIES



KIT EMERGENZA 3H 10V-54V


18005.99

KONE

103601.02

novalux

ITALIAN LIGHTING DESIGN SINCE 1948



KIT EMERGENZA 1H 10V-54V

18004.99



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.