



| | 16A 3pol. | 16A 4pol. | 16A 5pol. |
|-----------------------------|-----------|-----------|-----------|
| a | 90 | 90 | 90 |
| b | 170 | 170 | 170 |
| c | 77 | 77 | 77 |
| d | 137,5 | 137,5 | 137,5 |
| g | 6,5 | 6,5 | 6,5 |
| Øh | 5,5 | 5,5 | 5,5 |
| i | M20 | M20 | M20 |
| k | M25/20 | M25/20 | M25/20 |
| x | 188 | 189 | 190 |
| y | 90 | 90 | 90 |
| z | 108 | 114 | 122 |
| Leiter mm ² min. | 1,5 | 1,5 | 1,5 |
| Leiter mm ² max. | 4 | 4 | 4 |

Technische Änderungen vorbehalten

| | | | | | | | | | | |
|--------------------------------------|----------|----------|------|---|--|---|-----------|--------------------------|------------|---------|
| CAD-Zg.! Keine manuellen Änderungen! | | | | Bals Elektrotechnik GmbH & Co. KG Burgweg 22 57399 Kirchhundem www.bals.com | |  Einfach. Gut. Verbunden. | Werkstoff | | Oberfläche | |
| 11 | | | | | | | Blatt 1 | Anzahl d. Bl. 1 | Format A3 | |
| 10 | | | | | | Wandsteckdose 16A 3-5pol. spw. 170x90 | | Freim. Toler. ISO 2768-m | | Maßstab |
| 9 | | | | | | | | Ers.f.Zg. | | |
| 8 | | | | | | Zg.-Nummer: 1MB26 | | | | |
| 7 | | | | | | Typ-Nummer: | | Wz.Auftr.-Nr. | | |
| 6 | | | | | | | | | | |
| 5 | | | | | | | | | | |
| 4 | 42/17 | 18.10.19 | MAßm | | | | | | | |
| 3 | 117/06 | 23.02.07 | Bank | | | | | | | |
| Ausgabe | Änderung | Datum | Name | | | | | | | |