Entry, flat cable, for enclosures

Part no. RA-C1-DF 264243



| Product name | Eaton Moeller® series Rapid Link Accessory Accomplishment |
|-----------------------------|---|
| Part no. | RA-C1-DF |
| EAN | 4015082642433 |
| Product Length/Depth | 65 millimetre |
| Product height | 20 millimetre |
| Product width | 45 millimetre |
| Product weight | 0.033 kilogram |
| Compliances | CE |
| Product Tradename | Rapid Link |
| Product Type | Accessory |
| Product Sub Type | Accomplishment |
| | |
| Color | Black |
| Features | Watertight Halogen free |
| Functions | For bushing for flat cable in distributor module or control cabinet |
| Material | Plastic |
| | |
| Degree of protection | IP65 |
| Model | Other |
| Product category | Power supply |
| | |
| Operating temperature - min | -10 °C |
| Operating temperature - max | 55 °C |

Technical data FTIM 8.0

| Technical data ETIM 8.0 | | |
|---|------------------------|---|
| Cable and wire entry systems (EG000009) / Cable entry sleeve (EC000879) | | |
| Electric engineering, automation, process control engineering / Electrical installati | on, device / Connectio | n devices / Feed through spout (ecl@ss10.0.1-27-14-44-21 [ADI139007]) |
| Model | | Other |
| Suitable for cable gland | | No |
| Cable entry | | Long-slot |
| Number of cables | | 1-1 |
| Suitable for cable diameter | mm | 0 - 0 |
| Bore diameter | mm | 0 |
| For wall thickness | mm | 0 - 0 |
| Thread size (metric) | | 0 |
| Thread size PG | | 0 |
| Total length | mm | 65 |
| With strain relief | | No |
| Shrink technique | | No |
| Angle model | | No |
| Material | | Plastic |
| Material quality | | Polyvinyl chloride (PVC) |
| Surface protection | | Untreated |
| Halogen free | | Yes |
| Colour | | Black |
| Gastight | | No |
| Fire resistant | | No |

| Watertight | | Yes |
|---------------------------|----|----------|
| Degree of protection (IP) | | IP65 |
| Operating temperature | °C | -10 - 55 |