

Product designation				Rotary cam switches
Product type designation				GN32
General characteristics				
Switching diagram				07
N° of elements				2
Contact characteristics				
Rated insulation voltage Ui	IEC/EN	V	690	
	UL/CSA	V	600	
Rated impulse withstand voltage Uimp			kV	6
Conventional free air thermal current Ith	IEC/EN	A	32	
	UL/CSA	A	40	
Rated operational voltage			V	480
Maximum fuse size for short-circuit protection In (gG)	10kA	A	32	
	25kA	A	32	
	50kA	A	32	
Rated short time current Icw			1s	A
				800
Operational current Ie IEC/EN	AC1/AC21A			A
	AC15			32
Rated operational power in AC	110V			A
	220/230V			A
	380/400V			A
	660/690V			A
				2
Three-phase AC-3	220/230V		kW	7.5
	380/440V		kW	11
	500/690V		kW	11
Single-phase AC-3	110V		kW	2.2
	220/230V		kW	4
	380/440V		kW	6.5
Three-phase AC23A	220/230V		kW	8
	380/440V		kW	15
	500/690V		kW	18.5
Single-phase AC23A	110V		kW	2.2
	220/230V		kW	4
	380/440V		kW	7.5
Rated operational current in DC	DC21A			A
	48V			A
	60V			A
	110V			A
	220V			A
DC23A (poles in series)				0.9

24V	A	32 (1)
48V	A	32 (2)
60V	A	32 (3)
110V	A	15 (3)
220V	A	12 (4)

DC13

24V	A	32
48V	A	25
60V	A	16
110V	A	3
220V	A	0.5

Mechanical features

Terminals screw M4

Tightening torque for terminals max Nm 1.2

Conductor size

AWG - Rigid cable

min	AWG	16
Max	AWG	8

AWG - Flexible cable

min	AWG	16
Max	AWG	10

Conductor size (IEC) - Flexible cable

min	mm ²	1.5
Max	mm ²	4

Conductor size (IEC) - Rigid cable

min	mm ²	1.5
Max	mm ²	6

Mechanical life cycles 5x10⁶

UL technical data

Motor power for direct-on-line control

for three-phase motor

480V	HP	15
------	----	----

Ambient conditions

Temperature

Operating temperature

min	°C	-25
max	°C	+55

Storage temperature

min	°C	-40
max	°C	+70

Resistance & Protection

Frontal IP degree IP40

Terminals IP degree IP00

ETIM classification

ETIM 8.0

EC001029 -
Selector switch,
complete