

FILE NAME:

Material/Product Safety Data

Sheet

PRODUCT:

Ni-Cd Battery

DOCUMENT No.:

M/RONDA001

EDITION:

A5

DATE:

2016-1-4

EDITION	AMENDMENT	DATE OF ISSUE	
4	A0 Initial Publish	2012-09-01	
	A1 Changing the Company Name	2013-03-15	
	A2 Updating version	2014-01-07	
Α	A A3 Updating version		
	A4 Updated "Section 14 – transport	2015-8-28	
	information" .		
	A5 Updated section 1& section 14.	2016-1-4	

## Ronda Group Co., Ltd

Address: Block C&D, Shachongwei industrial zone, Huangzhuang, Jianshe third road, Jiangmen, Guangdong provience, China.

Tel.:86-750-8429388 Fax: 86-750-8429111 Postal code: 529728

E-mail: sales@ronda-battery.com Website: www.ronda-battery.com



**Notice:** If the document wasn't signed and stamped, the information (subject to change without prior notice) contained in this document is for reference only and should not be used as a criterion for product guarantee or warranty.



## **Section 1 – Chemical Product and Company Identification**

**Product Name:** Ni-Cd Battery (Sealed rechargeable Cells)

**Battery Type:** Series (According to the model size and design)

Manufacturer: Ronda Group Co., Ltd.

Address: Block C&D, Jianshe Third Road, Huangzhuang, Shachongwei

Industrial District, Jiangmen, Guangdong, China.

**Post Code:** 529000

**Tel:** 086-0750-8429388

**Emergency Telephone:** 086-0750-8429388

**Fax:** 086-0750-8429111

Web site: <a href="www.ronda-battery.com">www.ronda-battery.com</a>
<a href="mailto:sales@ronda-battery.com">Sales@ronda-battery.com</a>

Section 2 – Composition/Information on Indredient				
<b>Chemical Composition</b>	<b>Chemical Formula</b>	CAS No.	Weight (%)	
Nickel	Ni	7440-02-0	3~5	
Nickel Hydroxide	Ni(OH) <sub>2</sub>	12054-48-7	15~25	
Cadmium	Cd	7440-43-9	8~13	
Iron	Fe	7439-89-6	25~55	
Cobalt	Co	7440-48-4	2~6	
Potassium Hydroxide (Liquid)	КОН	1310-58-3	2.5~6	
PP Paper			1~5	
Cadmium Oxide	CdO	1306-19-0	8~18	
Water	H <sub>2</sub> O	231-791-2	4~9	

### **Section 3 – Hazards Identification**

No specific health hazards for normal use.

### **Routes of Entry**

Eyes, Skin, Inhalation, Ingestion.

#### **Health Hazards**

These chemicals are contained in a sealed can. Risk of exposure occurs only if the battery is mechanically or electrically abused. The most likely risk is acute exposure when a battery vents. Leaking material exposure to skin, eyes may cause irritation. Inhalation of fumes may cause respiratory irritation.



### Sign/Symptoms of Exposure

May be a reproductive hazard. Leaking can cause thermal and chemical burns upon contact with the skin.

## **Section 4 – First Aid Measures**

#### **Eyes**

Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

#### Skin

Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.

#### **Inhalation**

Remove from exposure and move to fresh air immediately. Use oxygen if available.

### Ingestion

Do not induce vomiting. Call a physician immediately.

# **Section 5 – Fire Fighting Measures**

Flash Point: N/A.

Auto-Ignition Temperature: N/A.

**Extinguishing Media** 

CO<sub>2</sub>, dry chemical.

### **Special Fire-Fighting Procedures**

Self-contained breathing apparatus.

#### **Unusual Fire and Explosion Hazards**

Cell may vent when subjected to excessive heat-exposing battery contents

### **Hazardous Combustion Products**

Carbon monoxide, carbon dioxide, other metallic oxide fumes. In case of PVC



sleeved products, the combustion releases chloride gas.

## **Section 6 – Accidental Release Measures**

### Steps to be Taken in case Material is Released or Spilled

If the battery is accidental broken and leaks out, wipe it up with a cloth, and dispose of it in a plastic bag and put into a steel can. The preferred response is to leave the area and allow the batteries to cool and vapors to dissipate. Provide maximum ventilation. Avoid skin and eye contact or inhalation of vapors. Remove spilled material with absorbent.

#### **Waste Disposal Method**

It is recommended to discharge the battery to the end, recycle zinc, copper and other metal, handing in the abandoned batteries to related department unified, and dispose of the batteries in accordance with approved local, state, and federal requirements. Consult state environmental protection agency and/or federal EPA.

# **Section 7 – Handling and Storage**

The batteries should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container. Do not short circuit terminals, or charge the battery, forced over-discharge, throw to fire. Do not crush or puncture the battery, or immerse in liquids.

#### Precautions to be taken in handling and storing

Avoid mechanical or electrical abuse. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change. Storage at high temperatures should be avoided. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.

#### **Other Precautions**

Do not short or install with incorrect polarity.



## Section 8 – Exposure Controls, Personal Protection

#### **Respiratory Protection**

In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting batteries. Respiratory Protection is not necessary under conditions of normal use.

### **Other Protective Clothing or Equipment**

Not necessary under conditions of normal use.

Personal Protection is recommended for venting batteries: Respiratory Protection, Protective Gloves, Protective Clothing and Safety Glass with side shields.

## **Section 9 – Physical and Chemical Properties**

Nominal Voltage: 1.2V

Rated Capacity: In accordance with the specification or the product marking.

**Appearance Characters:** Cylindrical, with odorless battery.

**Chemical Uses:** Chemical power.

# **Section 10 – Stability and Reactivity**

#### **Stability**

Stable.

#### **Conditions to Avoid**

Heating, fire, mechanical abuse and electrical abuse.

### **Hazardous Decomposition Products**

When exposed to fire or extreme heat, batteries may emit toxic fumes.

# **Section 11 – Toxicological Information**

Inhalation, skin contact and eye contact are possible when the battery is opened.



Exposure to internal contents, the corrosive fumes will be irritation to skin, eyes and mucous membranes. Overexposure can cause symptoms of non-fibroid lung injury and membrane irritation.

## **Section 12 – Ecological Information**

#### **Environment Effect**

When promptly used or disposed the battery does not present environmental hazard. In case of product destruction or opening, the metals content in a Ni-CD battery, and specifically the cadmium, are toxics for environment.

If not recycled, it must be disposed of in accordance with all state and local regulations.

# **Section 13 – Disposal Considerations**

### **Incineration**

Never incinerate Ni-CD batteries.

#### Landfill

Never dispose Ni-CD batteries as landfill.

#### Recycling

Ni-CD batteries can be fully recyclable. They are submitted to the European community

<u>directive 91-157/CE</u>. We recommend proper recycling of these batteries whenever possible.

### **Appropriate Method of Disposal of Substance or Preparation**

Dispose of the batteries in accordance with approved local, state, and federal requirements. Consult state environmental agency.

# **Section 14 – Transport Information**



Sealed Ni-CD batteries with sleeve are considered as "dry batteries" which transport is

not checked. They are not submitted to specific transport obligations for land, maritime

(IMDG) or air (IATA) transport, as they are protected against short-circuits.

Sealed Ni-CD batteries without sleeve are submitted to ADR prescription under UNO code 2800, except in case of qualified packaging use (IATA group 2 type).

Separate batteries when shipping to prevent short-circuiting. They should be packed in strong packaging for support during transport.

Seal Ni-CD batteries are compliant to Special Provision A123 which states: "An electrical battery or battery powered device having the potential of dangerous evolutions of heat that is not prepared so as to prevent a short-circuit."

According to IATA Dangerous Goods Regulations (DGR) 57<sup>th</sup> Editions, Seal Ni-CD batteries are not subject to IATA DGR.

# **Section 15 - Regulatory Information**

#### **Law Information**

《Dangerous Goods Regulation》

《Recommendations on the Transport of Dangerous Goods Model Regulations》

《International Maritime Dangerous Goods》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《Classification and code of dangerous goods》

《Occupational Safety and Health Act》 (OSHA)

《Toxic Substances Control Act》(TSCA)

《Consumer Product Safety Act》(CPSA)

《Federal Environmental Pollution Control Act》(FEPCA)

《The Oil Pollution Act》(OPA)

《Superfund Amendments and Reauthorization Act Title 111 (302/311/312/313》 (SARA)

《Resource Conservation and Recovery Act》 (RCRA)

《Safety Drinking Water Act》(CWA)

《California Proposition 65》

《Code of Federal Regulations》(CFR)

In accordance with all Federal, State and Local laws.



## **Section 16 – Additional Information**

The above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since this information may be applied under conditions

beyond our control and with which may be unfamiliar and since data made available subsequent to the data hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.