

Product type designation				GX20
General characteristics				
Switching diagram				92
N° of elements				2
Options				Enlarged front plate
Contact characteristics				
Rated insulation voltage Ui	IEC/EN	V		690
	UL/CSA	V		600
Rated impulse withstand voltage Uimp		kV		6
Conventional free air thermal current Ith	UL/CSA	A		15
		V		440
Rated operational voltage	25kA	A		16
Rated short time current Icw	1s	A		250
Operational current Ie IEC/EN	AC1/AC21A		A	20
	AC15	110V	A	10
		220/230V	A	8
		660/690V	A	3.7
Rated operational power in AC	Single-phase AC-3	380/440V	kW	3
	Three-phase AC23A	380/440V	kW	7.5
Single-phase AC23A	380/440V	kW	3.5	
Rated operational current in DC	DC21A	48V	A	20
		60V	A	20
		110V	A	4
		440V	A	0.25
	DC23A (poles in series)	24V	A	20 (1)
		48V	A	20 (2)
		60V	A	20 (3)
		110V	A	10 (3)
		220V	A	8 (4)
	DC13	24V	A	20
		48V	A	16
		60V	A	12
		110V	A	1
		220V	A	0.4
		440V	A	0.15
Mechanical features				
Terminals screw				M3

Tightening torque for terminals max	Nm	0.8
-------------------------------------	----	-----

Conductor size			
----------------	--	--	--

AWG - Rigid cable	min	AWG	20
	Max	AWG	14

AWG - Flexible cable	min	AWG	20
----------------------	-----	-----	----

Conductor size (IEC) - Flexible cable	min	mm ²	0.5
	Max	mm ²	2.5

Conductor size (IEC) - Rigid cable	Max	mm ²	2.5
------------------------------------	-----	-----------------	-----

Mechanical life	cycles	5x10 ⁶
-----------------	--------	-------------------

UL technical data

Motor power for direct-on-line control			
--	--	--	--

for three-phase motor	240V	HP	3
	480V	HP	5
	600V	HP	5

for single-phase motor	120V	HP	0.75
	240V	HP	1.5

Ambient conditions

Temperature			
-------------	--	--	--

Operating temperature	min	°C	-25
	max	°C	+55

Storage temperature	min	°C	-40
	max	°C	+70

Resistance & Protection

Frontal IP degree	IP65
-------------------	------

Terminals IP degree	IP20
---------------------	------

ETIM classification

ETIM 8.0	EC001029 - Selector switch, complete
----------	--------------------------------------