


# Product Environmental Profile

**Zelio Measurement Relay  
RM17... Control Relay**



## Product Environmental Profile – PEP

### Product overview

The main purpose of the RM17 Measurement and Control Relay is to monitor their own power supply, measured as a true rms value.

This range consists of RM17 J/T/U series. This range is to measure and monitor the abnormal operating conditions such as on current, voltage, frequency, phase, speed, temperature and liquid level that the machine will not be allowed to run when a fault is occurred. It allows the user to initiate the necessary corrective actions before serious and costly breakdowns can occur.


The representative product used for the analysis is RM17TE00. It is for 3-phase supply with power supply of 183 to 528 Vac.

The environmental impacts of this referenced product are representative of the impacts of the other products of the range which are developed with a similar technology.

The environmental analysis was performed in conformity with ISO 14040.

### Constituent materials

The mass of the product range is from 72 g and 130 g including packaging. It is 91.3 g for the RM17TE00. The constituent materials are distributed as follows:



### Substance assessment

Products of this range are designed in conformity with the requirements of the European RoHS Directive 2011/65/EU and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers - PBDE) as mentioned in the Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric [Green Premium website](http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page) . (<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page> )

### Manufacturing

The RM17 Measurement and Control Relay product range is manufactured at a Schneider Electric production site on which an ISO14001 certified environmental management system has been established.

## Distribution

The weight and volume of the packaging have been optimized, based on the European Union's packaging directive.

The RM17TE00 packaging weight is 20 g. It consists cardboard at 13.1 g and paper at 6.9 g.

## Use

The products of the RM17 Measurement and Control Relay range do not generate environmental pollution (noise, emissions) requiring special precautionary measures in standard use.

The electrical power consumption depends on the conditions under which the product is implemented and used. The electrical power consumed by RM17 Measurement and Control Relay range is between 0.2 W and 0.75 W. It is 30% of the time in active mode with a 0.6 W consumed power and 70% in standby mode with 0.2 W consumed power for the referenced RM17TE00.

The product range does not require special maintenance operations.

## End of life

At end of life, the products in the RM17 Measurement and Control Relay have been optimized to decrease the amount of waste and allow recovery of the product components and materials.

This product range contains one electronic card that should be separated from the stream of waste so as to optimize end-of-life treatment by special treatments. The location of these components and other recommendations are given in the End of Life Instruction document which is available for this product range on the Schneider-Electric Green Premium website [Green Premium website](http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page) (<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>).

The recyclability potential of the products has been evaluated using the “ECO DEEE recyclability and recoverability calculation method” (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).

According to this method, the potential recyclability ratio without packaging is: 30.3%.

As described in the recyclability calculation method this ratio includes only metals and plastics which have proven industrial recycling processes.

# Product Environmental Profile – PEP

## Environmental impacts

Life cycle assessment has been performed on the following life cycle phases: Materials and Manufacturing (M), Distribution (D), Installation (I) Use (U), and End of life (E).

Modeling hypothesis and method:

- The calculation was performed on RM17TE00.
- Product packaging is included.
- Installation components: no special components included.
- Scenario for the Use phase: this product range is included in the category energy consuming product. Assumed service lifetime is 10 years and use scenario is 30% of the time in active mode with a 0.6 W consumed power and 70% of the time in standby mode with a 0.2 W consumed power.
- The geographical representative area for the assessment is worldwide and the electrical power model used for calculation is European model.
- End of life impacts are based on a worst case transport distance to the recycling plant (1000km).

### Presentation of the product environmental impacts

Environmental indicators	Unit	RM17TE00					
		S = M + D + I + U + E	M	D	I	U	E
Air Acidification (AA)	kg H+ eq	3.92E-03	3.45E-04	2.95E-06	0.00E+00	3.58E-03	1.18E-06
Air toxicity (AT)	m <sup>3</sup>	4.66E+06	5.08E+05	4.38E+03	0.00E+00	4.15E+06	1.75E+03
Energy Depletion (ED)	MJ	3.60E+02	2.40E+01	2.21E-01	0.00E+00	3.35E+02	8.45E-02
Global Warming Potential (GWP)	kg CO <sub>2</sub> eq.	1.83E+01	1.70E+00	1.57E-02	0.00E+00	1.66E+01	6.00E-03
Hazardous Waste Production (HWP)	kg	3.06E-02	2.78E-02	1.94E-08	0.00E+00	2.84E-03	7.43E-09
Ozone Depletion Potential (ODP)	kg CFC-11 eq.	3.97E-06	1.94E-07	2.97E-11	0.00E+00	3.77E-06	1.14E-11
Photochemical Ozone Creation Potential (POCP)	kg C H <sub>4</sub> eq.	1.49E-03	4.65E-04	4.05E-06	0.00E+00	1.02E-03	1.49E-06
Raw Material Depletion (RMD)	Y-1	1.80E-14	1.77E-14	3.20E-19	0.00E+00	2.23E-16	1.23E-19
Water Depletion (WD)	dm <sup>3</sup>	5.25E+01	9.33E+00	1.63E-03	0.00E+00	4.32E+01	6.23E-04
Water Eutrophication (WE)	kg PO <sub>4</sub> <sup>3-</sup> eq.	3.16E-04	1.58E-04	2.91E-08	0.00E+00	1.57E-04	1.11E-08
Water Toxicity (WT)	m <sup>3</sup>	7.85E+00	4.70E-01	6.70E-03	0.00E+00	7.37E+00	2.56E-03

Life cycle assessment has been performed with the EIME software (Environmental Impact and Management Explorer), version 5.5 and with its database version 2015-12.

The Use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators.

According to this environmental analysis, proportionality rules may be used to evaluate the impacts of other products of this range: Depending on the impact analysis, the environmental indicators of other products in this family may be proportional extrapolated by energy consumption values. For RMD and HWP, impact may be proportional extrapolated by the mass of the product. For WE, 1/3 of the impact should be proportional to the mass of the product and 2/3 by the energy consumption values.

## System approach

As the products of the range are designed in accordance with the European RoHS Directive 2011/65/EU, they can be incorporated without any restriction in an assembly or an installation subject to this Directive.

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

## Glossary

**Air Acidification (AA)**

**Air Toxicity (AT)**

**Energy Depletion (ED)**

**Global Warming (GW)**

**Hazardous Waste Production (HWP)**

**Ozone Depletion (OD)**

**Photochemical Ozone Creation (POC)**

**Raw Material Depletion (RMD)**

**Water Depletion (WD)**

**Water Eutrophication (WE)**

**Water Toxicity (WT)**