

PRODUCT-DETAILS

JSHD4-2-AH

JSHD4-2-AH Three-position handheld device - Complete



Informations générales

Extension du type de produit	JSHD4-2-AH
Code de produit	2TLA019995R0800
EAN	7350024453423
Description courte	JSHD4-2-AH Three-position handheld device - Complete
Description longue	<p>The JSHD4-2-AH is an ergonomic three-position device which top part has LEDs, a front button and a top button, and which bottom part is equipped with a cable gland and a PCB with 10 screw connections.</p> <p>Three-position devices are used to allow a limited movement of the machine when the operator is in the dangerous area, for example during troubleshooting, test running and programming.</p>

Commande

Quantité minimum	1 pièce
Code douanier	85369095
Groupe de produit	JSHD4
Type de produit	Three-position handheld device - Complete
Fonction	Three-position device used to allow a limited movement of the machine when the operator is in the dangerous area.
Sub-Function	1 front and 1 top auxiliary buttons
Status Indicator	Oui

Downloads Préférés

Fiche produit, informations techniques	2TLC010001C0202
Instructions et manuels	2TLC172072M0201
Wiring Diagram	2TLC010143D0201
CAD Dimensional Drawing	2CDC001079B0201
Marketing Video	2TLC010018N0201

Dimensions

Produit Longueur Net	60 mm
Produit Hauteur Net	254 mm
Produit Largeur Net	34 mm
Poids net	0.314 kg

Safety Information

Performance Level (PL)	Up to e
B10d Value	Operations to Bottom Position 968 000 Operations to Middle Position 2 million

Technique

Interface de communication	Contacts
Configuration Connexion	Cable gland and 10 screw connection
Maximum Switching Current	Circuit principal 0.02 mA
Maximum Switching Voltage	Circuit principal 30 V
Minimum Switching Capacity	Main Circuit 8 mA, 10 VDC
Number of Contacts CO	2
Number of Contacts NC	0
Number of Contacts NO	0
Rated Operational Current DC-12 (I_{θ})	(24 V) 0.02 A
Tension	24 V DC
Informations techniques	Operating force: Approx. 15 N for three-position button (ON), Approx. 45 N for three-position button (OFF), Approx. 2.5 N for top/front pushbutton; Mechanical service life: 1 million cycles, top to middle position, 100 000 cycles, middle to bottom position, and top/front push button

Technique UL/CSA

Enclosure Type UL/CSA	1
-----------------------	---

Environnement

Température de l'air ambiant	Operation -10 ... +70 °C
Indice de protection	IP65

Matériau	Handle: Polyamide and Noryl Rubber: Neoprene
REACH Declaration	2CMT2022-006480
Informations RoHS	2CMT2022-006499
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Certificats et Déclarations (Numéro de document)

CQC Certificate	No certification needed
Certificat ecULus	2TLC010062D0201
Declaration of Conformity - CCC	No declaration needed
Déclaration de Conformité - CE	2TLC172022D0201
Declaration of Conformity - UKCA	2TLC010152D0201
SEMKO Certificate	2TLC172032D0201

Emballage

Emballage Niveau 1 Unités	1 pièce
Emballage Niveau 1 Largeur	286 mm
Emballage Niveau 1 Longueur	126 mm
Emballage Niveau 1 Hauteur	103 mm
Emballage Niveau 1 Poids	0.334 kg
Emballage Niveau 1 EAN	7350024453423

Classifications

eClass	V11.0 : 27371238
ETIM 7	EC002571 - Agreement switch
ETIM 8	EC002571 - Agreement switch
ETIM 9	EC002571 - Agreement switch
Code de classification d'objet	B
E-Number (Finland)	2307366

Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Produits pour la sécurité → Commandes → Poignée à trois positions JSHD4

