

Offset Tag fuse-links gG 415VAC/250VDC

LOW VOLTAGE IEC FUSES

BS FUSE-LINKS

The fuse complies with standard EN 60269-2 section II and standard BS 88 part 2. These fuses are designed for : “General purpose use” protection (gG type). This fuse range insures an excellent current limitation for all overloads on a large range of applications. Their size cannot allow exchange by other fuses of higher rating in their range. They are screwed into fuseholders or bolted directly onto busbars, or in fuse interruptors disconnectors.

FEATURES & BENEFITS

- Excellent current limitation for all overloads

APPLICATIONS

- These fuses are designed for : “General purpose use” protection (gG type)

STANDARDS

- EN 60269-2 section II



Offset Tag fuse-links gG 415VAC/250VDC

PRODUCT RANGE

Type A1 415VAC/250VDC gG

Catalog number	Rated voltage AC (IEC)	Rated voltage DC (IEC)	Rated current I_n	Pre-arcing I^2t	Clearing I^2t at Rated Voltage	Rated breaking capacity AC	Power dissipation at I_n
BEIT42V36	415 V	250 V	36 A	1000 A ² s	4000 A ² s	80 A	2.8 W
BEIT42V40	415 V	250 V	40 A	1300 A ² s	4200 A ² s	80 A	3 W
BEIT42V50	415 V	250 V	50 A	2600 A ² s	8750 A ² s	80 A	3.6 W
BEIT42V63	415 V	250 V	63 A	4000 A ² s	13900 A ² s	80 A	4.7 W