




Product designation Product type designation			Pushbutton actuators, spring return, with symbol LPCB11
General characteristics			
Colour			White
Type of positions			Flush pushbutton
Material			Polyamide
IEC degree of protection			IP66, IP67 and IP69K
Mechanical features			
Operating force		kg-lb	<0.5Kg / 1.1lb
Mechanical life		cycles	5000000
Fixing			Without mounting adapter
Mounting adapter			LPXAU120
Weight		g	25
UL technical data			
UL degree of protection			Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions			
Temperature			
Operating temperature			
	min	°C	-25
	max	°C	+70
Storage temperature			
	min	°C	-40
Dimensions	max	°C	+85

## Dimensions



## Certifications and compliance

## Compliance

CSA C22.2 n° 14 IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1

LPCB1128



## LPCB1128 PUSHBUTTON ACTUATOR, SPRING RETURN, WITH SYMBOL Ø22MM PLATINUM SERIES CHROMED PLASTIC, FLUSH, II/WHITE

	UL508
Certificates	
	CCC
	cULus
	EAC
	RINA
ETIM classification	

**ETIM 8.0** 

EC000221 -Front element for push button