

PRODUCT-DETAILS

# TF42-0.23

## TF42-0.23 Thermal Overload Relay 0.17 ... 0.23

A



### Informations générales

Extension du type de produit	TF42-0.23
Code de produit	1SAZ721201R1009
EAN	4013614398001
Description courte	TF42-0.23 Thermal Overload Relay 0.17 ... 0.23 A

Description longue	The TF42-0.23 thermal overload relay is an economic electromechanical protection device for the main circuit. It offers reliable and fast protection for motors in the event of overload or phase failure. The device has trip class 10. Further features are the temperature compensation, trip contact (NC), signal contact (NO), automatic- or manual reset selectable, trip-free mechanism, STOP function and a trip indication. The overload relays are connected directly to the block contactors. Single mounting kits are available as accessory.
--------------------	---

### Commande

Quantité minimum	1 pièce
Code douanier	85364900

### Downloads Préférés

Fiche produit, informations techniques	2CDC106023D0201
Instructions et manuels	2CDC106022M6802

Instructions et manuels (Partie 2)	1SAC200017M0002
Ex Operating Instructions	2CDC106076M6801
Time-Current Characteristic Curve	1SAZ700506F0003
CAD Dimensional Drawing	2CDC001079B0201
Schéma dimensionnel	1SAZ700405F0001

## Dimensions

Produit Largeur Net	45 mm
Produit Hauteur Net	88.3 mm
Produit Longueur Net	70.5 mm
Poids net	0.13 kg

## Technique

Setting Range	0.17 ... 0.23 A
Tension	Circuit auxiliaire 600 V AC/DC Circuit principal 690 V AC Circuit principal 600 V DC
Courant nominal de fonctionnement ( $I_g$ )	0.23 A
Fréquence assignée (f)	Circuit auxiliaire 50 Hz Circuit auxiliaire 60 Hz Circuit auxiliaire DC Circuit principal 50 Hz Circuit principal 60 Hz
Tension assignée de tenue aux chocs ( $U_{imp}$ )	Circuit auxiliaire 6 kV Circuit principal 6 kV
Tension assignée d' isolement ( $U_i$ )	690 V
Nombre de pôles	3
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Number of Protected Poles	3
Courant thermique conventionnel à l'air libre ( $I_{th}$ )	Auxiliary Circuit NC 6 A Auxiliary Circuit NO 4 A
Courant assignée d' emploi AC-15 ( $I_g$ )	(120 V) NC 3 A (120 V) NO 0.5 A (240 V) NC 3 A (240 V) NO 0.5 A (400 V) NC 0.75 A (400 V) NO 0.5 A (500 V) NC 0.75 A (500 V) NO 0.5 A
Courant assignée d' emploi DC-13 ( $I_g$ )	(125 V) NC 0.55 A (125 V) NO 0.55 A (24 V) NC 1.25 A

	(24 V) NO 1.25 A (250 V) NC 0.27 A (250 V) NO 0.27 A (500 V) NC 0.15 A (500 V) NO 0.15 A (60 V) NC 0.55 A (60 V) NO 0.55 A
Indice de protection	IP20
Degré de pollution	3
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup> Flexible 1/2x 0.75 ... 1 mm <sup>2</sup> Flexible 1/2x 1 ... 2.5 mm <sup>2</sup> Rigid 1/2x 0.75 ... 4 mm <sup>2</sup>
Connecting Capacity Main Circuit	Flexible with Ferrule 1/2x 0.75 ... 4 mm <sup>2</sup> Flexible with Insulated Ferrule 1/2x 0.75 ... 4 mm <sup>2</sup> Flexible 1/2x 0.75 ... 4 mm <sup>2</sup> Rigid 1/2x 0.75 ... 4 mm <sup>2</sup>
Couple de serrage	Auxiliary Circuit 1 ... 1.2 N·m Main Circuit 1.5 ... 2.5 N·m
Wire Stripping Length	Auxiliary Circuit 9 mm Main Circuit 12 mm
Recommended Screw Driver	Circuit principal Pozidriv 2
Power Loss	at Rated Operating Conditions per Pole 1.1 ... 2.0 W
Adapté pour	AF09 AF12 AF16 AF26 AF30 AF38
Normes et standards	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1

## Technique UL/CSA

Maximum Operating Voltage UL/CSA	Circuit principal 600 V AC
Contact Rating UL/CSA	(NC:) B600 (NC:) Q600 (NO:) Q600 (NO:) D300
Connecting Capacity Main Circuit UL/CSA	Flexible 1/2x 18-10 AWG Stranded 1/2x 18-10 AWG
Connecting Capacity Auxiliary Circuit UL/CSA	Flexible 1/2x 18-12 AWG Stranded 1/2x 18-12 AWG
Tightening Torque UL/CSA	Auxiliary Circuit 9 ... 11 in·lb Main Circuit 13 ... 22 in·lb

## Environnement

Température de l'air ambiant	Operation -25 ... +60 °C Operation Compensated -25 ... +60 °C Storage -50 ... +80 °C
---------------------------------	--

Ambient Air Temperature Compensation	Oui
Altitude de fonctionnement maximale autorisée	2000 m
Résistance aux chocs selon CEI 60068-2-27	11 ms Pulse 25g
Resistance to Vibrations acc. to IEC 60068-2-6	5g / 3 ... 150 Hz
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

---

## Eco Transparence

Informations environnementales	1SAA200057H0009
--------------------------------	-----------------

---

## Certificats et Déclarations (Numéro de document)

Certificat ABS	1SAA941001-0102
Certificat ATEX	1SAA941001-3901
Certificat BV	1SAA941001-0203
CB Certificate	1SAA941009-2001
CQC Certificate	CQC2011010309464423
Declaration of Conformity - CCC	2020980304001788
Déclaration de Conformité - CE	1SAD101100-3503
Declaration of Conformity - UKCA	1SAD201100-3503
DNV GL Certificate	1SAA941001-0302
EAC Certificate	1SAA941002-2701
Certificat GL	1SAA941007-0401
IECEX Certificate	1SAA941003-4001
Certificat LR	1SAA941001-0502
Certificat RINA	1SAA941000-0802
Certificat RMRS	1SAA941000-0704
Certificat UL	E48139-20090126

---

## Emballage

Emballage Niveau 1 Unités	carton 1 pièce
Emballage Niveau 1 Largeur	48 mm
Emballage Niveau 1 Hauteur	92 mm
Emballage Niveau 1 Longueur	78 mm
Emballage Niveau 1 Poids	0.145 kg
Emballage Niveau 1 EAN	4013614398001

Emballage Niveau 2 Unités	carton 40 pièce
Emballage Niveau 2 Largeur	280 mm
Emballage Niveau 2 Hauteur	210 mm
Emballage Niveau 2 Longueur	395 mm
Emballage Niveau 2 Poids	7.346 kg
Emballage Niveau 2 EAN	4013614440038

## Classifications

Code de classification d'objet	F
ETIM 4	EC000106 - Thermal overload relay
ETIM 5	EC000106 - Thermal overload relay
ETIM 6	EC000106 - relais de surcharge thermique
ETIM 7	EC000106 - Thermal overload relay
ETIM 8	EC000106 - Thermal overload relay
eClass	V11.0 : 27371501
UNSPSC	39122330
Code de catégorie granulaire IDEA (IGCC)	5366 >> Thermal overload relay
E-Number (Finland)	3706112
E-Number (Sweden)	3211956

## Accessories

Identifiant	Description	Type	Quantity	Unit Of Measure
1SAZ701902R0001	DB42 Single Mounting Kit	DB42	1	piece
1SAX101911R1001	DRS-F-01 Remote Reset Coil	DRS-F-01	1	piece
1SAX101911R1002	DRS-F-02 Remote Reset Coil	DRS-F-02	1	piece
1SAX101911R1003	DRS-F-03 Remote Reset Coil	DRS-F-03	1	piece
1SAX101911R1004	DRS-F-04 Remote Reset Coil	DRS-F-04	1	piece
1SAZ701904R1001	DRS-F-TF-01 Remote Coil	DRS-F-TF-01	1	piece
1SAZ701904R1002	DRS-F-TF-02 Remote Coil	DRS-F-TF-02	1	piece
1SAZ701904R1003	DRS-F-TF-03 Remote Coil	DRS-F-TF-03	1	piece
1SAZ701904R1004	DRS-F-TF-04 Remote Coil	DRS-F-TF-04	1	piece
1SAZ701903R1001	WRH-F Holder	WRH-F	1	piece
1SAZ701903R1011	WRB-400 Bowden Wire	WRB-400	1	piece
1SAZ701903R1012	WRB-600 Bowden Wire	WRB-600	1	piece
1SAZ701903R1013	WRB-1000 Bowden Wire	WRB-1000	1	piece
1SAZ701903R1030	WRBG Gasket	WRBG	1	piece
1SFA616162R1014	KPR3-101L Reset push button	KPR-101L	1	piece

---

## Catégories

---

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Contacteurs → Relais de protection contre les surcharges

