

## Features

Use: Indoor  
Type of installation: SUSPENDED  
Emission: DIRECT/INDIRECT  
Optics: OPAL  
Colour: WHITE  
Dimming: ON/OFF  
Emergency: NO  
L: 1200mm  
A: 1200mm  
H: 90mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 28kg

## Tech data

Luminaire input power: 213.4W  
Luminaire luminous flux: 22740lm  
Direct luminous flux: 15911lm  
Indirect luminous flux: 6829lm  
IP: 40  
Insulation class: I  
Supply voltage: 220-240V 50/60Hz  
SELV: No

## Source

Light source: LED  
Source power: 192W  
Source luminous flux: 31174lm  
Colour temperature: 3000K  
CRI: >80  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1


## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)

## MOUNTING ACCESSORIES


---



ROTO: ALIMENTAZIONE L1200 3P. BIA

104423.01


---



ROTO: ALIMENTAZIONE L1200 5P. BIA.

104424.01


---



ROTO: ALIMENTAZIONE L3000 3P. BIA.

104425.01

---



ROTO: ALIMENTAZIONE L3000 5P. BIA.

104426.01

---



ROTO: D=1200 KIT 4 SOSP. L3000

104429.99

---