
ENERGY AND AUTOMATION

DOUBLE-TOUCH ACTUATOR, SPRING RETURN Ø22MM PLATINUM SERIES METAL, 2 FLUSH PUSHBUTTONS. BOTH SPRING RETURN, GREEN - RED



Product designation Product type designation			Double-touch actuators, spring return - two flush pushbuttons LPSB71
General characteristics			
Colour			Green/Red
Type of positions			Double-touch with two flush pushbuttons
Material			Aluminium and zinc alloy for metal parts and polyamide for plastic parts
IEC degree of protection			IP66, IP67 and IP69K
Mechanical features			
Mechanical life		cycles	1000000
Fixing			Without mounting adapter
Mounting adapter			LPXAU120M
UL technical data			
UL degree of protection			Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions			
Temperature			
Operating temperature			
	min	°C	-25
	max	°C	+70
Storage temperature		°C	40
	min max	°C °C	-40 +85
Dimensions	IIIaX		+0J



Certifications and compliance

Compliance

CSA C22.2 n° 14 IEC/EN/BS 60947-1

IEC/EN/BS 60947-5-1

UL508





DOUBLE-TOUCH ACTUATOR, SPRING RETURN Ø22MM PLATINUM SERIES METAL, 2 FLUSH PUSHBUTTONS. BOTH SPRING RETURN, GREEN - RED

ENERGY AND AUTOMATION

Certificates

cULus

ETIM classification

ETIM 8.0

EC000029 -Push-switch button