

PRODUCT-DETAILS

OTE75T4M

OTE75T4M EMC safety switch



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | OTE75T4M |
| Code de produit | 1SCA022812R4670 |
| EAN | 6417019274614 |
| Description courte | OTE75T4M EMC safety switch |
| Description longue | <p>EMC safety switch, 4-p. 415V AC23 80A, 37kW. Mounted auxiliary contact: 1NO0NC. Plastic enclosure. IP65. Black Selector handle. Interlocked cover. Defeatable interlocking. The enclosure in the OTE series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries are threaded and have knock out holes for 2 parallel cables and one control cable, both from top and bottom. The handle is padlockable and made for three padlocks. The interlocking can be by-passed, for thermographing etc. The switch is made for 5 wire system, and have a fixed neutral terminal and PE terminal. The EMC protection is utilized by a metal plate in the bottom, connected to the cable shield with clamps, included in the delivery. No EMC glands needed.</p> |

Valeur Circulaire

| | |
|---|-----------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 1SCC340076D0201 |
| Informations RoHS | 1SCC340075D0201 |
| Toxic Substances Control Act - TSCA | 1SCC340095D0201 |

Commande

| | |
|------------------|--------------|
| Quantité minimum | 1 pièce |
| Code douanier | 85363030 |
| Pays d'origine | Finland (FI) |

Downloads Préférés

| | |
|--|------------------------------------|
| Fiche produit, informations techniques | 1SCC340015C0201 |
| Instructions et manuels | 1SCC340003M0016 9AKK108466A4485 |
| Mechanical Drawings | OTPK402014SM50.stp |

Dimensions

| | |
|----------------------|--------|
| Produit Largeur Net | 200 mm |
| Produit Hauteur Net | 400 mm |
| Produit Longueur Net | 140 mm |
| Poids net | 3.7 kg |

Technique

| | |
|---|---|
| Rated Operational Current AC-22A (I_e) | (380 ... 415 V) 100 A (500 V) 100 A (690 V) 100 A |
| Rated Operational Current AC-23A (I_e) | (380 ... 415 V) 80 A (500 V) 60 A (690 V) 40 A |
| Rated Operational Power AC-23A (P_e) | (380 ... 415 V) 37 kW (500 V) 37 kW (690 V) 37 kW |
| Conventional Thermal Current (I_{the}) | Fully Enclosed 115 A |
| Tension assignée d'isolement (U_i) | acc. to IEC/EN 60664-1 750 V |
| Tension | Circuit principal 750 V |
| Rated Short-Circuit Making Capacity (I_{cm}) | (690 V AC) 3.6 kA |
| Courant assigné de courte durée admissible (I_{cw}) | for 1 s 2.5 kA |
| Power Loss | at Rated Operating Conditions per Pole 4 W |
| Degré de pollution | 3 |
| Handle Color | Black |
| Handle Type | Selector handle |
| Normes et standards | IEC 60947-1, -3 |
| Fonctions spéciales | EMC |
| Nombre de pôles | 4 |
| Neutral Type | Fixed and switchable neutral |
| Connecting Capacity Main Circuit | Screw Clamp 10 ... 70 mm ² Screw Clamp / PE Terminal 4pc, 10 ... 70 mm ² |
| Section de câble | 10 ... 70 mm ² |
| Cable Entry Position | Top and/or Bottom |
| Cable Outlets Per Side | 2xM50+M16 / 2xM50+M16 |
| Indice de protection | acc. to IEC 60529 IP65 |

| | |
|------------------------------------|--------------------|
| Résistance aux chocs | Housing IK08 |
| Matériau du boîtier | Plastic |
| Maximum Mounted Auxiliary Contacts | 2 NO, 2 NC |
| Mounted Auxiliary Contacts | 1 NO, 0 NC |
| Number of Auxiliary Contacts NC | 0 |
| Number of Auxiliary Contacts NO | 1 |
| Couple de serrage | Main Circuit 6 N·m |

Technique UL/CSA

| | |
|-------------------|--------------------|
| Couple de serrage | Main Circuit 6 N·m |
|-------------------|--------------------|

Environnement

| | |
|-------------------------------------|-----------------------------------|
| Statut RoHS | Following EU Directive 2011/65/EU |
| Toxic Substances Control Act - TSCA | 1SCC340095D0201 |

Certificats et Déclarations (Numéro de document)

| | |
|--------------------------------|-----------------|
| Certificat BV | 1SCC340018D0204 |
| Déclaration de Conformité - CE | 1SCC340004D2705 |
| DNV GL Certificate | 1SCC340045D0203 |
| REACH Declaration | 1SCC340076D0201 |

Emballage

| | |
|-----------------------------|---------------|
| Emballage Niveau 1 Unités | box 1 pièce |
| Emballage Niveau 1 Largeur | 213 mm |
| Emballage Niveau 1 Longueur | 417 mm |
| Emballage Niveau 1 Hauteur | 197 mm |
| Emballage Niveau 1 Poids | 3.8 kg |
| Emballage Niveau 1 EAN | 6417019274614 |

Classifications

| | |
|--------------------------------|--|
| Code de classification d'objet | Q |
| ETIM 7 | EC000216 - Switch disconnecter |
| ETIM 8 | EC000216 - Switch disconnecter |
| ETIM 9 | EC000216 - Switch disconnecter (low voltage) |
| eClass | V11.1 : 27371403 |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| E-Number (Norway) | 1429423 |

Catégories

Produits basse tension → Interrupteurs et appareillage à fusibles en coffret → Interrupteurs de sécurité en coffret → Enclosed Safety Switches

