
SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1>0<2 WITH DIFFERENT KEY CODE. WITHDRAL AT 0



Product designation				Selector switch actuator key - 3 position
Product type designat				LPFS37
General characteristic	os en la companya de			
Colour				Black
Type of positions				Selector switch
Material				Aluminium and zinc alloy
IEC degree of protect	tion			IP66, IP67 and IP69K
Mechanical features				
Mechanical life			cycles	1000000
Fixing				Without mounting adapter
Mounting adapter				LPXAU120M
UL technical data				
UL degree of protection				Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-25
		max	°C	+70
	Storage temperature			
		min	°C	-40
		max	°C	+85
Dimoneione				

Dimensions



Certifications and compliance

Compliance

CSA C22.2 n° 14 IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1

UL508

Certificates

cULus

ETIM classification





SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1>0<2 WITH DIFFERENT KEY CODE. WITHDRAL AT 0

ETIM 8.0

EC002611 -Control switch