

PRODUCT-DETAILS

OT63FT3

OT63FT3 SWITCH-DISCONNECTOR



Informations générales

Extension du type de produit	OT63FT3
Code de produit	1SCA105382R1001
EAN	6417019393186
Description courte	OT63FT3 SWITCH-DISCONNECTOR
Description longue	3-pole, front operated, door mounted switch-diconnector / non-fusible diconnect switch with protected clamp terminals, handle is not included

Valeur Circulaire

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Informations environnementales	1SCC301263D0201
Environmental Product Declaration - EPD	1SCC301279D0201
REACH Declaration	1SCC011021D0201
Informations RoHS	1SCC011020D0201
Toxic Substances Control Act - TSCA	1SCC011025D0201

Eco Transparence

Environmental Product
Declaration - EPD

1SCC301279D0201

Commande

Quantité minimum	10 pièce
Code douanier	85365080
Pays d'origine	Finland (FI)

Downloads Préférés

Fiche produit, informations techniques	1SCC301020C0201
Instructions et manuels	1SCC301063M0006
Mechanical Drawings	1SCC301454F0001 1SCC301453F0001 OT63-80FT3.igs
Environmental Product Declaration - EPD	1SCC301279D0201

Dimensions

Produit Largeur Net	65 mm
Produit Hauteur Net	72 mm
Produit Longueur Net	69 mm
Poids net	0.26 kg

Technique

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 63 A (500 V) 63 A (690 V) 63 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 63 A (500 V) 63 A (690 V) 63 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 63 A (500 V) 45 A (690 V) 20 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 11 kW (400 ... 415 V) 22 kW (500 V) 22 kW (690 V) 15 kW
Courant thermique conventionnel à l'air libre (I_{th})	$\Theta = 40\text{ °C}$ 63 A
Conventional Thermal Current (I_{the})	Fully Enclosed 63 A
Tension assignée de tenue aux chocs (U_{imp})	8 kV
Tension assignée d'isolement (U_i)	acc. to IEC/EN 60664-1 750 V
Tension	Circuit principal 750 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V) 2.1 kA
Courant assigné de courte durée admissible (I_{cw})	for 1 s 1.5 kA
Rated Conditional Short-	(100 A fuse, $\leq 415\text{ V}$) 50 kA (100 A fuse, 500 V) 100 kA

Circuit Current (I_{nc})	(80 A fuse, 690 V) 50 kA
Power Loss	at Rated Operating Conditions per Pole 2.8 W
Degré de pollution	3
Handle Type	Handle and shaft not included
Switches Operating Mechanism	Mechanism on Top of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Mode de fonctionnement	Front operated
Normes et standards	IEC 60947-3 / UL 508 / CSA C22.2 No. 14
Fonctions spéciales	No
Type de montage	Door mounting
Nombre de pôles	3
Section de câble	Cu 1.5 ... 35 mm ²
Indice de protection	Front IP20
Type de borne	Screw Terminals
Couple de serrage	acc. IEC 60947-1 2 N·m
Durabilité mécanique	20000
Lock Type	No

Technique UL/CSA

Maximum Operating Voltage UL/CSA	600 V
Ampere Rating	60 A
Puissance nominale UL/CSA	(110 ... 120 V AC) Single Phase 2 Hp (240 V AC) Single Phase 7.5 Hp (440 ... 480 V AC) Single Phase 15 Hp (550 ... 600 V AC) Single Phase 15 Hp (220 ... 240 V AC) Three Phase 15 Hp (440 ... 480 V AC) Three Phase 30 Hp (550 ... 600 V AC) Three Phase 30 Hp
Couple de serrage	acc. IEC 60947-1 2 N·m
Tightening Torque UL/CSA	18 in·lb

Environnement

Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations environnementales	1SCC301263D0201
Toxic Substances Control Act - TSCA	1SCC011025D0201

Certificats et Déclarations (Numéro de document)

Certificat ATEX	No certification needed
Déclaration de Conformité - CE	1SCC301167D2704
REACH Declaration	1SCC011021D0201
Certificat UL	cULus certificate OT16-80
VDE Certificate	No certification needed

Emballage

Emballage Niveau 1 Unités	box 1 pièce
Emballage Niveau 1 Largeur	80 mm
Emballage Niveau 1 Longueur	84 mm
Emballage Niveau 1 Hauteur	76 mm
Emballage Niveau 1 Poids	0.28 kg
Emballage Niveau 1 EAN	6417019393186

Classifications

Code de classification d'objet	Q
ETIM 7	EC000216 - Switch disconnector
ETIM 8	EC000216 - Switch disconnector
ETIM 9	EC000216 - Switch disconnector (low voltage)
UNSPSC	39122233
Code de catégorie granulaire IDEA (IGCC)	5290 >> Disconnect switch
eClass	V11.1 : 27371403
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601455
E-Number (Sweden)	3170947

Catégories

Produits basse tension → Interrupteurs → Interrupteurs-sectionneurs

