



# P-30 PCB

1058A2.20

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



## Features

Use: Indoor  
Type of installation: SUSPENDED, CEILING MOUNTED  
Emission: ADJUSTABLE  
Optics: SPOT  
Beam: 14°  
Colour: CAFFE  
Dimming: ON/OFF  
Emergency: NO  
L: 800mm  
A: 31mm  
H: 31mm  
Made in: ITALY  
Warranty: 5 years

## Tech data

Luminaire input power: 14.9W  
Luminaire luminous flux: 856lm  
IP: 20  
Insulation class: I  
Supply voltage: 220-240V 50/60Hz  
SELV: Si

## Source

Light source: LED  
Source power: 9W  
Source luminous flux: 1015lm  
Colour temperature: 3000K  
CRI: >90  
Colour tolerance: 2 Step MacAdam  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

## Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.

# P-30 PCB

1058A2.20

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948

## SCREENS

---




P-30: DIFF. OPALE L=6500

**103315.99**

## COMPLETION ACCESSORIES

---




P-30: SNODO 3P PER PCB/STRIP CAFFE

**105853.20**




P-30: COVER ANGOLO L CAFFE

**103329.20**




P-30: TESTATA PER INSTALL.VERT. CAF

**1058D8.20**



P-30: ANGOLO T PLAFONE-SOSP CAFFE

**103331.20**



P-30: SNODO NO CAVI CAFFE

**105854.20**



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.

# P-30 PCB

1058A2.20

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



P-30: COVER ANGOLO T CAFFE

103333.20



P-30: ANGOLO L PLAFONE-SOSP-PARETE CAFFE


103327.20



P-30: TESTATE PLAF/SOSP/PAR/SPOT CAFFE

103361.20

## MOUNTING ACCESSORIES




P-30: ROSONE LATER. ALIM L=1200 3P BIA

103320.01




P-30: CAVO DI SOSPENSIONE

103318.99



P-30: ROSONE CARTON. ALIM L1200 3P CAFFE

103319.20



P-30: ROSONE LATER. ALIM L1200 3P CAFFE

103320.20




Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.

# P-30 PCB

1058A2.20

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



P-30: ROSONE CARTON. ALIM L=1200 3P BIA

**103319.01**



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.