



Product designation			Selector switch actuator key - 2 position
Product type designation			LPFS32
General characteristics			
Colour			Black
Type of positions			Selector switch
Material			Aluminium and zinc alloy
IEC degree of protection			IP66, IP67 and IP69K
Mechanical features			
Mechanical life		cycles	1000000
Fixing			Without mounting adapter
Mounting adapter			LPXAU120M
UL technical data			
UL degree of protection			Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions			
Temperature			
Operating temperature			
	min	°C	-25
	max	°C	+70
Storage temperature			
	min	°C	-40
	max	°C	+85
Dimensions			

34.7-(1.37") (0.99") (0.88") (0.88") (0.88") (0.88") (0.88")

	Key
Certifications and	compliance
Compliance	
	CSA C22.2 n° 14
	IEC/EN/BS 60947-1
	IEC/EN/BS 60947-5-1
	UL508
Certificates	
	cULus
ETIM classification	n



**LPFS321R3433E** SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 2 POSITION, 0 - 1 WITH DIFFERENT KEY CODE

ETIM 8.0

EC002611 -Control switch