

Power supply 1.5m for RA-/C3A



Part no. RA-C4-X/C3-1M5
116961

Product name		Eaton Moeller® series Rapid Link Accessory Power connection cable
Part no.		RA-C4-X/C3-1M5
EAN		4015081167012
Product Length/Depth		1.5 metre
Product height		300 millimetre
Product width		300 millimetre
Product weight		0.55 kilogram
Compliances		CE
Product Tradename		Rapid Link
Product Type		Accessory
Product Sub Type		Power connection cable
Color		Gray
Features		Oil resistant (acc. EN 60811-404) Connector system system-oriented
Fitted with:		Protective conductor
Functions		For connecting the device with the round cable junction
Degree of protection		Other
Nominal current		6.6 A
Nominal voltage - min		380 V
Nominal voltage - max		480 V
Product category		Power supply
Permissible ambient temperature - min		-10 °C
Permissible ambient temperature - max		55 °C
Cable type		5 x 1.5 mm ² , halogen free, with ferrules, power plug and IP65 gasket
Outer diameter - approximate		10 mm
Outer sheath material		Other

Technical data ETIM 8.0

Batteries, chargers and power cords (EG000053) / Power cord (EC001576)		
Electric engineering, automation, process control engineering / Cable, wire / Ready-made low-voltage line / Extension line (low-voltage line) (ec@ss10.0.1-27-06-04-02 [AAB665013])		
Connection 1		Other
Connection 2		Other
Connector system system-oriented		Yes
Number of cores		5
Nominal cross section conductor	mm ²	1.5
Length	m	1.5
Material outer sheath		Other
Temperature resistance	°C	-10 - 55
Nominal current	A	6.6
Nominal voltage	V	380 - 480
Frequency	Hz	50 - 60
Colour outer sheath		Grey
Spiralized cable		No
With protective conductor		Yes

Degree of protection (IP)			Other
Oil resistant (according to EN 60811-404)			Yes
With cord switch			No
Outer diameter approx.		mm	10
Reaction-to-fire class according to EN 13501-6			None
Smoke development class according to EN 13501-6			None
Euro class flaming droplets/particles according to EN 13501-6			None
Euro class acidity according to EN 13501-6			None