ENERGY AND AUTOMATION

PUSH-PUSH BUTTON ACTUATOR Ø22MM PLATINUM SERIES METAL, EXTENDED. PUSH ON-PUSH OFF, BLUE



Product designation			Push-push button actuators
Product type designation			LPSQ20
General characteristics			
Colour			Blue
Type of positions			Extended pushbutton. Push on-push off
Material			Aluminium and zinc alloy
IEC degree of protection			IP66, IP67 and IP69K
Mechanical features			
Operating force		kg-lb	<0.5Kg / 1.1lb
Mechanical life - Push-Push actuators		cycles	500000
Fixing			Without mounting adapter
Mounting adapter			LPXAU120M
UL technical data			
UL degree of protection			Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions			
Temperature			
Operating temperature			
	min	°C	-25
	max	°C	+70
Storage temperature		0.0	40
	min	°C	-40
Dimensions	max	U	+85
16.7—1 (0.65°)			

(0.66")

Certifications and compliance

Comp	

CSA C22.2 n° 14 IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1

UL508 Certificates

cULus

ETIM classification



PUSH-PUSH BUTTON ACTUATOR Ø22MM PLATINUM SERIES METAL, EXTENDED. PUSH ON-PUSH OFF, BLUE **ENERGY AND AUTOMATION**

ETIM 8.0

EC000029 -Push-switch button