

Product designation				Rotary cam switches
Product type designation				GN63
General characteristics				
Switching diagram				59
Contact characteristics				
Rated insulation voltage U_i	IEC/EN	V	690	
	UL/CSA	V	600	
Rated impulse withstand voltage U_{imp}			kV	6
Conventional free air thermal current I_{th}	UL/CSA	A	60	
			V	480
Rated operational voltage			V	480
Maximum fuse size for short-circuit protection I_n (gG)	10kA	A	63	
	25kA	A	63	
	50kA	A	63	
Rated short time current I_{cw}			1s	A
				1600
Operational current I_e IEC/EN	AC1/AC21A			A
	AC15			63
Rated operational power in AC	110V			A
	220/230V			A
	380/400V			A
	660/690V			A
				4
Three-phase AC-3	220/230V	kW	11	
	380/440V	kW	18.5	
	500/690V	kW	18.5	
Single-phase AC-3	110V	kW	3.7	
	220/230V	kW	6.5	
	380/440V	kW	11.5	
Three-phase AC23A	220/230V	kW	12.5	
	380/440V	kW	30	
	500/690V	kW	30	
Single-phase AC23A	110V	kW	3.7	
	220/230V	kW	7.5	
	380/440V	kW	12.5	
Rated operational current in DC	DC21A			
	48V	A	63	
DC23A (poles in series)	60V	A	50	
	110V	A	8	
	220V	A	1	
	24V	A	50 (1)	
	48V	A	50 (2)	

	60V	A	50 (3)
	110V	A	25 (3)
	220V	A	15 (4)
DC13			
	24V	A	63
	48V	A	40
	60V	A	28
	110V	A	3.3
Mechanical features			
Terminals screw			M5
Tightening torque for terminals max		Nm	2
Conductor size			
AWG - Rigid cable			
	min	AWG	14
	Max	AWG	6
AWG - Flexible cable			
	min	AWG	14
	Max	AWG	8
Conductor size (IEC) - Flexible cable			
	min	mm ²	2.5
	Max	mm ²	10
Conductor size (IEC) - Rigid cable			
	min	mm ²	2.5
	Max	mm ²	16
Mechanical life		cycles	5x10 ⁶
UL technical data			
Motor power for direct-on-line control for three-phase motor			
	480V	HP	25
Ambient conditions			
Temperature			
Operating temperature			
	min	°C	-25
	max	°C	+55
Storage temperature			
	min	°C	-40
	max	°C	+70
Resistance & Protection			
Frontal IP degree			IP40
Terminals IP degree			IP00
ETIM classification			
ETIM 8.0			EC001029 - Selector switch, complete