

Features

Use: Outdoor
Type of installation: INCASSO A PAVIMENTO
Emission: INDIRECT
Optics: SPOT
Beam: 50°
Colour: BRUSHED STAINLESS AISI 316
Dimming: ON/OFF
Emergency: NO
L: 95mm
A: 95mm
H: 115mm
Warranty: 5 years
Weight: 0.545kg

Tech data

Luminaire input power: 5W
Luminaire luminous flux: 359lm
IP: 67
Insulation class: I
Supply voltage: 220-240V 50/60Hz

Source

Light source: LED
Source power: 5W
Colour temperature: 3000K
CRI: >90
LED lifespan: 30000h L70 B20

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-13

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.


[View more product info](#)

ZENIT

111304.09

novalux
ITALIAN LIGHTING DESIGN SINCE 1948

MOUNTING ACCESSORIES



ZENIT: CASSAFORMA

111305.99



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.